



### **PSAA15W-120V Information**



For Reference Only

**Part Number** PSAA15W-120V **Manufacturer** Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 12V 15W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **PSAA15W-120V Specifications**

Manufacturer Part Number         PSAA15W-120V           Manufacturer         Phihong USA           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         PSAA15W           Region Utilized         International           Form         Desktop (Class II)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.25A           Power (Watts)         15W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         3.20" L x 1.97" W x 1.17" H (81.2mm x 50.0mm x 29.8mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         PSAA15W           Region Utilized         International           Form         Desktop (Class II)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.25A           Power (Watts)         15W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         3.20" L x 1.97" W x 1.17" H (81.2mm x 50.0mm x 29.8mm)	Manufacturer Part Number	PSAA15W-120V
AC DC Desktop, Wall Adapters  Package - Series PSAA15W Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.25A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension  AC DC Desktop, Wall Adapters  PSAA15W  Adapters PSAA15W  No Load Power (Sold Separately)  12V  12V  12V  12V  12V  12V  12V  12	Manufacturer	Phihong USA
Package         -           Series         PSAA15W           Region Utilized         International           Form         Desktop (Class II)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.25A           Power (Watts)         15W           No Load Power Consumption         300mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         3.20" L x 1.97" W x 1.17" H (81.2mm x 50.0mm x 29.8mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSAA15WRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1.25APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.20" L x 1.97" W x 1.17" H (81.2mm x 50.0mm x 29.8mm)		AC DC Desktop, Wall Adapters
Region Utilized International  Form Desktop (Class II)  Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 1.25A  Power (Watts) 15W  No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 3.20" L x 1.97" W x 1.17" H (81.2mm x 50.0mm x 29.8mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 1.25A  Power (Watts) 15W  No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 3.20" L x 1.97" W x 1.17" H (81.2mm x 50.0mm x 29.8mm)	Series	PSAA15W
Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 1.25A  Power (Watts) 15W  No Load Power Consumption 300mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 3.20" L x 1.97" W x 1.17" H (81.2mm x 50.0mm x 29.8mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $12\text{V}$ Current - Output (Max) $1.25\text{A}$ Power (Watts) $15\text{W}$ No Load Power Consumption $300\text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{mm}$ I.D. $x \leq 5.5\text{mm}$ O.D. $x \leq 9.5\text{mm}$ Size / Dimension $3.20^{\circ}$ L $x \leq 1.97^{\circ}$ W $x \leq 1.17^{\circ}$ H ( $81.2\text{mm}$ $x \leq 50.0\text{mm}$ $x \leq 29.8\text{mm}$ )	Form	Desktop (Class II)
Voltage - Output (Max)  Current - Output (Max)  1.25A  Power (Watts)  15W  No Load Power Consumption  Polarization  Polarization  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  12V  1.25A  1.25A  1.25A  Power (Watts)  15W  No Load Power Consumption  300mW (Max)  Positive Center  1TE (Commercial)  Level V  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  3.20" L x 1.97" W x 1.17" H (81.2mm x 50.0mm x 29.8mm)	Input Type	Cord (Sold Separately)
Current - Output (Max)  1.25A  Power (Watts)  15W  No Load Power Consumption  Positive Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  3.20" L x 1.97" W x 1.17" H (81.2mm x 50.0mm x 29.8mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  15W  No Load Power Consumption  300mW (Max)  Polarization  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  3.20" L x 1.97" W x 1.17" H (81.2mm x 50.0mm x 29.8mm)	Voltage - Output	12V
No Load Power Consumption $300 \text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{mm}$ I.D. $x$ 5.5mm O.D. $x$ 9.5mmSize / Dimension $3.20^{\circ}\text{L}$ x $1.97^{\circ}\text{W}$ x $1.17^{\circ}\text{H}$ ( $81.2 \text{mm}$ x $50.0 \text{mm}$ x $29.8 \text{mm}$ )	Current - Output (Max)	1.25A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{mm}$ I.D. $x$ 5.5mm O.D. $x$ 9.5mmSize / Dimension $3.20^{\circ}$ L $x$ 1.97" W $x$ 1.17" H (81.2mm $x$ 50.0mm $x$ 29.8mm)	Power (Watts)	15W
Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $3.20^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.17^{\circ}\text{H} (81.2\text{mm} \times 50.0\text{mm} \times 29.8\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $3.20^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.17^{\circ}\text{H} (81.2\text{mm} \times 50.0\text{mm} \times 29.8\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $3.20^{\circ}\text{L x }1.97^{\circ}\text{W x }1.17^{\circ}\text{H }(81.2\text{mm x }50.0\text{mm x }29.8\text{mm})$	Applications	ITE (Commercial)
Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         3.20" L x 1.97" W x 1.17" H (81.2mm x 50.0mm x 29.8mm)	Efficiency	Level V
Size / Dimension 3.20" L x 1.97" W x 1.17" H (81.2mm x 50.0mm x 29.8mm)	Operating Temperature	0°C ~ 40°C
· · · ·	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	3.20" L x 1.97" W x 1.17" H (81.2mm x 50.0mm x 29.8mm)
•		Report errors?

#### **PSAA15W-120V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **PSAA15W-120V Payment Methods**



















## **PSAA15W-120V Shipping Methods**













If you have any question about PSAA15W-120V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com