



Heisener.com

PSAA18U-150-R-CN2 Information

Part Number PSAA18U-150-R-CN2

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 15V 18W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSAA18U-150-R-CN2 Specifications

Manufacturer Part Number PSAA18U-150-R-CN2 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) Rekage - Series PSAA18U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 1.2A Power (Watts) 18W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSAA18U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 15 V Current - Output (Max) 1.2A Power (Watts) 18W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Manufacturer Part Number	PSAA18U-150-R-CN2
Package-SeriesPSAA18URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output15VCurrent - Output (Max)1.2APower (Watts)18WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Manufacturer	Phihong USA
Package - Series PSAA18U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 1.2A Power (Watts) 18W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSAA18URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output15VCurrent - Output (Max)1.2APower (Watts)18WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 1.2A Power (Watts) 18W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 1.2A Power (Watts) 18W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Series	PSAA18U
Input TypeCord (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 15 V Current - Output (Max) 1.2A Power (Watts) 18W No Load Power Consumption 300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. $x 5.5\text{mm}$ O.D. $x 10.0\text{mm}$ Size / Dimension 4.06° L $x 1.93^{\circ}$ W $x 1.32^{\circ}$ H (103.0mm x 49.0mm x 33.5mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 15V Current - Output (Max) 1.2A Power (Watts) 18W No Load Power Consumption 300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.06° L x 1.93° W x 1.32° H (103.0mm x 49.0mm x 33.5mm)	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 1.2A Power (Watts) No Load Power Consumption Negative Center Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 15V 12A 18W No Load Power Consumption Negative Center ITE (Commercial) Level V Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 1.2A Power (Watts) 18W No Load Power Consumption Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 18W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Voltage - Output	15V
No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.06^{\circ}\text{L} \times 1.93^{\circ}\text{W} \times 1.32^{\circ}\text{H} (103.0 \text{mm} \times 49.0 \text{mm} \times 33.5 \text{mm})$	Current - Output (Max)	1.2A
Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.06^{\circ}\text{L} \times 1.93^{\circ}\text{W} \times 1.32^{\circ}\text{H} (103.0 \text{mm} \times 49.0 \text{mm} \times 33.5 \text{mm})$	Power (Watts)	18W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.06^{\circ}\text{L} \times 1.93^{\circ}\text{W} \times 1.32^{\circ}\text{H} (103.0 \text{mm} \times 49.0 \text{mm} \times 33.5 \text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.06^{\circ}\text{L} \times 1.93^{\circ}\text{W} \times 1.32^{\circ}\text{H} (103.0\text{mm} \times 49.0\text{mm} \times 33.5\text{mm})$	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.06^{\circ}\text{L} \text{ x } 1.93^{\circ}\text{ W x } 1.32^{\circ}\text{H} (103.0\text{mm x } 49.0\text{mm x } 33.5\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Efficiency	Level V
Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)
		Report errors?

PSAA18U-150-R-CN2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSAA18U-150-R-CN2 Payment Methods



















PSAA18U-150-R-CN2 Shipping Methods













If you have any question about PSAA18U-150-R-CN2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com