

Heisener.com

# PSAA18U-150-R-CNR4

### PSAA18U-150-R-CNR4 Information

Part Number PSAA18U-150-R-CNR4

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 15V 18W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PSAA18U-150-R-CNR4 Specifications

Manufacturer Part Number         PSAA18U-150-R-CNR4           Manufacturer         Phihong USA           Category         Power Supplies - External/Internal (Off-Board)           Package         -           Series         PSAA18U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         15V           Current - Output (Max)         1.2A           Power (Watts)         18W           No Load Power Consumption         300mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mm           Size / Dimension         4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesPSAA18URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output15 VCurrent - Output (Max)1.2APower (Watts)18WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mmSize / Dimension4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Manufacturer Part Number	PSAA18U-150-R-CNR4
Package-SeriesPSAA18URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output15VCurrent - Output (Max)1.2APower (Watts)18WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mmSize / Dimension4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Manufacturer	Phihong USA
Package         -           Series         PSAA18U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         15V           Current - Output (Max)         1.2A           Power (Watts)         18W           No Load Power Consumption         300mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mm           Size / Dimension         4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSAA18URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output15VCurrent - Output (Max)1.2APower (Watts)18WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mmSize / Dimension4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 1.2A Power (Watts) 18W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 15V  Current - Output (Max) 1.2A  Power (Watts) 18W  No Load Power Consumption 300mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Series	PSAA18U
Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 15V  Current - Output (Max) 1.2A  Power (Watts) 18W  No Load Power Consumption 300mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $15\text{V}$ Current - Output (Max) $1.2\text{A}$ Power (Watts) $18\text{W}$ No Load Power Consumption $300\text{mW}$ (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, $1.35\text{mm}$ I.D. x $3.5\text{mm}$ O.D. x $10.0\text{mm}$ Size / Dimension $4.06^{\circ}$ L x $1.93^{\circ}$ W x $1.32^{\circ}$ H ( $103.0\text{mm}$ x $49.0\text{mm}$ x $33.5\text{mm}$ )	Form	Desktop (Class I)
Voltage - Output  Current - Output (Max)  1.2A  Power (Watts)  No Load Power Consumption  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension  15V  1.2A  1.2A  1.2A  1.2B  1.2C  1.2	Input Type	Cord (Sold Separately)
Current - Output (Max)  1.2A  Power (Watts)  18W  No Load Power Consumption  Negative Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension  4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $18W$ No Load Power Consumption $300mW$ (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug R/A, $1.35mm$ I.D. $x$ $3.5mm$ O.D. $x$ $10.0mm$ Size / Dimension $4.06$ " L $x$ $1.93$ " W $x$ $1.32$ " H ( $103.0mm$ $x$ $49.0mm$ $x$ $33.5mm$ )	Voltage - Output	15V
No Load Power Consumption 300mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension $4.06^{\circ}\text{L} \times 1.93^{\circ}\text{W} \times 1.32^{\circ}\text{H} (103.0 \text{mm} \times 49.0 \text{mm} \times 33.5 \text{mm})$	Current - Output (Max)	1.2A
Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension $4.06^{\circ}\text{L} \times 1.93^{\circ}\text{W} \times 1.32^{\circ}\text{H} (103.0 \text{mm} \times 49.0 \text{mm} \times 33.5 \text{mm})$	Power (Watts)	18W
Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension $4.06^{\circ}\text{L} \times 1.93^{\circ}\text{W} \times 1.32^{\circ}\text{H} (103.0 \text{mm} \times 49.0 \text{mm} \times 33.5 \text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension $4.06^{\circ}\text{L} \times 1.93^{\circ}\text{W} \times 1.32^{\circ}\text{H} (103.0\text{mm} \times 49.0\text{mm} \times 33.5\text{mm})$	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension $4.06^{\circ}\text{L} \times 1.93^{\circ}\text{W} \times 1.32^{\circ}\text{H} (103.0\text{mm} \times 49.0\text{mm} \times 33.5\text{mm})$	Applications	ITE (Commercial)
Output Connector         Barrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mm           Size / Dimension         4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Efficiency	Level V
Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 1.35mm I.D. x 3.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)
		Report errors?

#### PSAA18U-150-R-CNR4 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PSAA18U-150-R-CNR4 Payment Methods



















## PSAA18U-150-R-CNR4 Shipping Methods













If you have any question about PSAA18U-150-R-CNR4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com