

Heisener.com

# PSAA18U-240-R-CNR2

### PSAA18U-240-R-CNR2 Information

Part Number PSAA18U-240-R-CNR2

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 24V 18W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## PSAA18U-240-R-CNR2 Specifications

Manufacturer Part Number         PSAA18U-240-R-CNR2           Manufacturer         Phihong USA           Category         Power Supplies - External/Internal (Off-Board)           Rekage         -           Series         PSAA18U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         750mA           Power (Watts)         18W           No Load Power Consumption         300mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm           Size / Dimension         4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesPSAA18URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)750mAPower (Watts)18WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Manufacturer Part Number	PSAA18U-240-R-CNR2
Package-SeriesPSAA18URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)750mAPower (Watts)18WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Manufacturer	Phihong USA
Package         -           Series         PSAA18U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         750mA           Power (Watts)         18W           No Load Power Consumption         300mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm           Size / Dimension         4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSAA18URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)750mAPower (Watts)18WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 750mA Power (Watts) 18W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 750mA Power (Watts) 18W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Series	PSAA18U
Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 24V  Current - Output (Max) 750mA  Power (Watts) 18W  No Load Power Consumption 300mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $24\text{V}$ Current - Output (Max) $750\text{mA}$ Power (Watts) $18\text{W}$ No Load Power Consumption $300\text{mW}$ (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension $4.06^{\circ}\text{ L x 1.93^{\circ} W x 1.32^{\circ} H (103.0mm x 49.0mm x 33.5mm)}$	Form	Desktop (Class I)
Voltage - Output  Current - Output (Max)  750mA  Power (Watts)  18W  No Load Power Consumption  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension  24V  750mA  18W  No Load Power Consumption  Negative Center  ITE (Commercial)  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Input Type	Cord (Sold Separately)
Current - Output (Max)  Power (Watts)  18W  No Load Power Consumption  Negative Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension  750mA  750mA  750mA  750mA  750mA  750mA  800mW (Max)  Negative Center  ITE (Commercial)  Level V  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $18W$ No Load Power Consumption $300mW$ (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension $4.06$ " L x $1.93$ " W x $1.32$ " H ( $103.0mm$ x $49.0mm$ x $33.5mm$ )	Voltage - Output	24V
No Load Power Consumption $300  \text{mW}$ (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension $4.06''  \text{L} \times 1.93''  \text{W} \times 1.32''  \text{H} (103.0  \text{mm} \times 49.0  \text{mm} \times 33.5  \text{mm})$	Current - Output (Max)	750mA
Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension $4.06^{\circ}\text{L} \times 1.93^{\circ}\text{W} \times 1.32^{\circ}\text{H} (103.0 \text{mm} \times 49.0 \text{mm} \times 33.5 \text{mm})$	Power (Watts)	18W
Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension $4.06^{\circ}\text{L} \times 1.93^{\circ}\text{W} \times 1.32^{\circ}\text{H} (103.0\text{mm} \times 49.0\text{mm} \times 33.5\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.06^{\circ}\text{L} \text{ x } 1.93^{\circ}\text{ W x } 1.32^{\circ}\text{ H } (103.0\text{mm x } 49.0\text{mm x } 33.5\text{mm})$	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.06^{\circ}\text{L} \text{ x } 1.93^{\circ}\text{ W x } 1.32^{\circ}\text{H} (103.0\text{mm x } 49.0\text{mm x } 33.5\text{mm})$	Applications	ITE (Commercial)
Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm           Size / Dimension         4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Efficiency	Level V
Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)
		Report errors?

### PSAA18U-240-R-CNR2 Guarantees



### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PSAA18U-240-R-CNR2 Payment Methods























## PSAA18U-240-R-CNR2 Shipping Methods













If you have any question about PSAA18U-240-R-CNR2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com