



PSAA30R-240-R-CN5 Information

Heisener.com

Part Number PSAA30R-240-R-CN5

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 24V 30W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSAA30R-240-R-CN5 Specifications

Manufacturer Part Number PSAA30R-240-R-CN5 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSAA30R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output (Max) 1.25A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 3.26" L x 2.17" W x 1.54" H (82.7mm x 55.0mm x 39.1mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSAA30R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 1.25A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 3.26" L x 2.17" W x 1.54" H (82.7mm x 55.0mm x 39.1mm)	Manufacturer Part Number	PSAA30R-240-R-CN5
Package - Series PSAA30R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 1.25A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 3.26" L x 2.17" W x 1.54" H (82.7mm x 55.0mm x 39.1mm)	Manufacturer	Phihong USA
Package-SeriesPSAA30RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)1.25APower (Watts)30WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mmSize / Dimension3.26" L x 2.17" W x 1.54" H (82.7mm x 55.0mm x 39.1mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSAA30RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)1.25APower (Watts)30WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mmSize / Dimension3.26" L x 2.17" W x 1.54" H (82.7mm x 55.0mm x 39.1mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 1.25A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 3.2.6" L x 2.17" W x 1.54" H (82.7mm x 55.0mm x 39.1mm)	Package	-
Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 1.25A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, $0.7 \text{mm I.D. x 2.5mm O.D. x 10.0mm}$ Size / Dimension 3.26" L x 2.17" W x 1.54" H (82.7 mm x 55.0 mm x 39.1 mm)	Series	PSAA30R
Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 1.25A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 3.26" L x 2.17" W x 1.54" H (82.7mm x 55.0mm x 39.1mm)	Region Utilized	International
Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 1.25A Power (Watts) No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 3.26" L x 2.17" W x 1.54" H (82.7mm x 55.0mm x 39.1mm)	Form	Wall Mount
Voltage - Output Current - Output (Max) 1.25A Power (Watts) No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 24V 1.25A 1.25A Negative Center Negative Center Negative Center Negative Center 1.25 (Commercial) 1.25 (Commer	Input Type	Multi-Blade (Sold Separately)
Current - Output (Max) Power (Watts) 30W No Load Power Consumption Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 1.25A 30W 30W 30W Annual Connector Negative Center ITE (Commercial) Level VI O°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm 3.26" L x 2.17" W x 1.54" H (82.7mm x 55.0mm x 39.1mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 3.26" L x 2.17" W x 1.54" H (82.7mm x 55.0mm x 39.1mm)	Voltage - Output	24V
No Load Power Consumption 300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension $3.26''$ L x $2.17''$ W x $1.54''$ H (82.7mm x 55.0mm x 39.1mm)	Current - Output (Max)	1.25A
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Power (Watts)	30W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension $3.26^{\circ}\text{L} \times 2.17^{\circ}\text{W} \times 1.54^{\circ}\text{H} (82.7\text{mm} \times 55.0\text{mm} \times 39.1\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension $3.26^{\circ}\text{L} \times 2.17^{\circ}\text{W} \times 1.54^{\circ}\text{H} (82.7\text{mm} \times 55.0\text{mm} \times 39.1\text{mm})$	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension $3.26^{\circ}\text{L} \times 2.17^{\circ}\text{W} \times 1.54^{\circ}\text{H} (82.7\text{mm} \times 55.0\text{mm} \times 39.1\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 3.26" L x 2.17" W x 1.54" H (82.7mm x 55.0mm x 39.1mm)	Efficiency	Level VI
Size / Dimension 3.26" L x 2.17" W x 1.54" H (82.7mm x 55.0mm x 39.1mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	3.26" L x 2.17" W x 1.54" H (82.7mm x 55.0mm x 39.1mm)
		Report errors?

PSAA30R-240-R-CN5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSAA30R-240-R-CN5 Payment Methods



















PSAA30R-240-R-CN5 Shipping Methods













If you have any question about PSAA30R-240-R-CN5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com