

## **PSAA60M-480 Information**



For Reference Only

Part Number PSAA60M-480 Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 48V 60W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **PSAA60M-480 Specifications**

Manufacturer Part Number         PSAA60M-480           Manufacturer         Phihong USA           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         PSAA60M           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         48V           Current - Output (Max)         1.25A           Power (Watts)         60W           No Load Power Consumption         500mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)    Report errors?			
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         PSAA60M           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         48V           Current - Output (Max)         1.25A           Power (Watts)         60W           No Load Power Consumption         500mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Manufacturer Part Number	PSAA60M-480	
AC DC Desktop, Wall Adapters  Package - Series PSAA60M Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC  Voltage - Output 48V Current - Output (Max) 1.25A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension  5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Manufacturer	Phihong USA	
Package         -           Series         PSAA60M           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         100 ~ 240 VAC           Voltage - Output         48V           Current - Output (Max)         1.25A           Power (Watts)         60W           No Load Power Consumption         500mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
SeriesPSAA60MRegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output48VCurrent - Output (Max)1.25APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)		AC DC Desktop, Wall Adapters	
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 48V Current - Output (Max) 1.25A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Package	-	
Form Desktop (Class I) Input Type Cord (Sold Separately)  Voltage - Input 100 ~ 240 VAC  Voltage - Output 48V  Current - Output (Max) 1.25A  Power (Watts) 60W  No Load Power Consumption 500mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Series	PSAA60M	
Input Type Cord (Sold Separately)  Voltage - Input 100 ~ 240 VAC  Voltage - Output 48V  Current - Output (Max) 1.25A  Power (Watts) 60W  No Load Power Consumption 500mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Region Utilized	International	
Voltage - Input  Voltage - Output  48V  Current - Output (Max)  1.25A  Power (Watts)  No Load Power Consumption  500mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Form	Desktop (Class I)	
Voltage - Output (Max) 1.25A  Power (Watts) 60W  No Load Power Consumption 500mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Input Type	Cord (Sold Separately)	
Current - Output (Max)  1.25A  Power (Watts)  60W  No Load Power Consumption  500mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Voltage - Input	100 ~ 240 VAC	
Power (Watts)  No Load Power Consumption  500mW (Max)  Polarization  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Voltage - Output	48V	
No Load Power Consumption $500 \text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{mm}$ I.D. $x$ 5.5mm O.D. $x$ 9.5mmSize / Dimension $5.12$ " L $x$ 2.36" W $x$ 1.30" H (130.0mm $x$ 60.0mm $x$ 32.0mm)	Current - Output (Max)	1.25A	
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{mm I.D. x 5.5 mm O.D. x 9.5 mm}$ Size / Dimension $5.12$ " L x $2.36$ " W x $1.30$ " H ( $130.0 mm x 60.0 mm x 32.0 mm$ )	Power (Watts)	60W	
Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0\text{mm} \times 60.0\text{mm} \times 32.0\text{mm})$	No Load Power Consumption	500mW (Max)	
Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0 \text{mm} \times 60.0 \text{mm} \times 32.0 \text{mm})$	Polarization	Positive Center	
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0\text{mm} \times 60.0\text{mm} \times 32.0\text{mm})$	Applications	ITE (Commercial)	
Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Efficiency	Level V	
Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Operating Temperature	0°C ~ 40°C	
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm	
Report errors?	Size / Dimension	5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	
		Report error	s?

#### PSAA60M-480 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PSAA60M-480 Payment Methods



















### PSAA60M-480 Shipping Methods













If you have any question about PSAA60M-480, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com