



### PSAC30U-050-R-CN2 Information



For Reference Only

Part Number PSAC30U-050-R-CN2

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 5V 30W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### PSAC30U-050-R-CN2 Specifications

Manufacturer Part Number         PSAC30U-050-R-CN2           Manufacturer         Philong USA           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         PSAC30U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output (Max)         4A           Power (Watts)         20W           No Load Power Consumption         300mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm           Size / Dimension         4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         PSAC30U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         5V           Current - Output (Max)         4A           Power (Watts)         20W           No Load Power Consumption         300mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm           Size / Dimension         4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Manufacturer Part Number	PSAC30U-050-R-CN2
AC DC Desktop, Wall Adapters  Package - Series PSAC30U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension  AC DC Desktop, Wall Adapters PSAC30U  International AC DC Desktop, Wall Adapters PSAC30U  International AC DC Desktop, Wall Adapters PSAC30U  International AAC DC Desktop, Wall Adapters PSAC30U  International AAC DC Desktop, Wall Adapters PSAC30U  International AAC DC Desktop, Wall Adapters PSAC30U  International AC DC Desktop  PSAC30U  International AC DC Desktop  PSAC30U  International AC DC Desktop  International AC DC Desktop  PSAC30U  International AC DC Desktop  International AC DC DC DESKtop  International AC DC	Manufacturer	Phihong USA
Package         -           Series         PSAC30U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         5V           Current - Output (Max)         4A           Power (Watts)         20W           No Load Power Consumption         300mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm           Size / Dimension         4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSAC30URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Package	-
Form Desktop (Class I)  Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V  Current - Output (Max) 4A  Power (Watts) 20W  No Load Power Consumption 300mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension 4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Series	PSAC30U
Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V  Current - Output (Max) 4A  Power (Watts) 20W  No Load Power Consumption 300mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension 4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Region Utilized	International
Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Form	Desktop (Class I)
Voltage - Output (Max) 4A  Power (Watts) 20W  No Load Power Consumption 300mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension 4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Input Type	Cord (Sold Separately)
Current - Output (Max)  Power (Watts)  20W  No Load Power Consumption  300mW (Max)  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension  4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  20W  No Load Power Consumption  300mW (Max)  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension  4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Voltage - Output	5V
No Load Power Consumption 300mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension $4.07^{\circ}\text{L} \text{ x } 1.65^{\circ}\text{W} \text{ x } 1.13^{\circ}\text{ H } (103.4\text{mm x } 42.0\text{mm x } 28.7\text{mm})$	Current - Output (Max)	4A
PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension $4.07$ " L x $1.65$ " W x $1.13$ " H ( $103.4$ mm x $42.0$ mm x $28.7$ mm)	Power (Watts)	20W
Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension $4.07^{\circ}\text{L} \text{ x } 1.65^{\circ}\text{ W x } 1.13^{\circ}\text{ H } (103.4\text{mm x } 42.0\text{mm x } 28.7\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension $4.07^{\circ}\text{L} \times 1.65^{\circ}\text{W} \times 1.13^{\circ}\text{H} (103.4\text{mm} \times 42.0\text{mm} \times 28.7\text{mm})$	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.07$ " L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension 4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Efficiency	Level V
Size / Dimension 4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 10.0mm
	Size / Dimension	4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)
Report errors?		Report errors?

#### PSAC30U-050-R-CN2 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PSAC30U-050-R-CN2 Payment Methods



















## PSAC30U-050-R-CN2 Shipping Methods













If you have any question about PSAC30U-050-R-CN2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com