



#### PSAC30U-050-R-CNR2 Information

www.helsener.com

For Reference Only

Part Number PSAC30U-050-R-CNR2

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 5V 30W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### PSAC30U-050-R-CNR2 Specifications

Manufacturer Part NumberPSAC30U-050-R-CNR2ManufacturerPhihong USACategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesPSAC30URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         PSAC30U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         5V           Current - Output (Max)         4A           Power (Watts)         20W           No Load Power Consumption         300mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm           Size / Dimension         4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Manufacturer Part Number	PSAC30U-050-R-CNR2
AC DC Desktop, Wall Adapters  Package - Series PSAC30U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC  Voltage - Output Voltage - Output SV Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension  AC DC Desktop, Wall Adapters PSAC30U International Inte	Manufacturer	Phihong USA
Package         -           Series         PSAC30U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         5V           Current - Output (Max)         4A           Power (Watts)         20W           No Load Power Consumption         300mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm           Size / Dimension         4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSAC30URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V  Current - Output (Max) 4A  Power (Watts) 20W  No Load Power Consumption 300mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension 4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Series	PSAC30U
Input TypeCord (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $5\text{V}$ Current - Output (Max) $4\text{A}$ Power (Watts) $20\text{W}$ No Load Power Consumption $300\text{mW}$ (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension $4.07$ " L x $1.65$ " W x $1.13$ " H ( $103.4$ mm x $42.0$ mm x $28.7$ mm)	Region Utilized	International
Voltage - Input  90 ~ 264 VAC  Voltage - Output  5V  Current - Output (Max)  4A  Power (Watts)  No Load Power Consumption  300mW (Max)  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension  4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Form	Desktop (Class I)
Voltage - Output  Current - Output (Max)  4A  Power (Watts)  No Load Power Consumption  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension  5V  Current - Output (Max)  4A  Power (Watts)  Negative Center  ITE (Commercial)  Level V  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Input Type	Cord (Sold Separately)
Current - Output (Max)  4A  Power (Watts)  20W  No Load Power Consumption  300mW (Max)  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension  4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $20W$ No Load Power Consumption $300mW$ (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension $4.07$ " L x $1.65$ " W x $1.13$ " H ( $103.4mm$ x $42.0mm$ x $28.7mm$ )	Voltage - Output	5V
No Load Power Consumption 300mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension $4.07^{\circ}\text{L} \times 1.65^{\circ}\text{W} \times 1.13^{\circ}\text{H} (103.4\text{mm} \times 42.0\text{mm} \times 28.7\text{mm})$	Current - Output (Max)	4A
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Power (Watts)	20W
Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension $4.07^{\circ}\text{L} \text{ x } 1.65^{\circ}\text{ W x } 1.13^{\circ}\text{ H } (103.4\text{mm x } 42.0\text{mm x } 28.7\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension $4.07^{\circ}\text{L} \text{ x } 1.65^{\circ}\text{W} \text{ x } 1.13^{\circ}\text{H} (103.4\text{mm x } 42.0\text{mm x } 28.7\text{mm})$	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.07^{\circ}\text{L x }1.65^{\circ}\text{W x }1.13^{\circ}\text{H }(103.4\text{mm x }42.0\text{mm x }28.7\text{mm})$	Applications	ITE (Commercial)
Output Connector         Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm           Size / Dimension         4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Efficiency	Level V
Size / Dimension 4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)
		Report errors?

#### PSAC30U-050-R-CNR2 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PSAC30U-050-R-CNR2 Payment Methods



















## PSAC30U-050-R-CNR2 Shipping Methods













If you have any question about PSAC30U-050-R-CNR2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com