



PSAC30U-120-R-CNR2 Information

www.helsener.com

For Reference Only

Part Number PSAC30U-120-R-CNR2

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 30W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSAC30U-120-R-CNR2 Specifications

Manufacturer Part Number PSAC30U-120-R-CNR2 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) Rekage - Series PSAC30U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSAC30U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Manufacturer Part Number	PSAC30U-120-R-CNR2
AC DC Desktop, Wall Adapters Package - Series PSAC30U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension AC DC Desktop, Wall Adapters PSAC 30U International In	Manufacturer	Phihong USA
Package - Series PSAC30U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSAC30URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)2.5APower (Watts)30WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)2.5APower (Watts)30WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Series	PSAC30U
Input TypeCord (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.07 " L x 1.65 " W x 1.13 " H (103.4mm x 42.0mm x 28.7mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. $x 5.5\text{mm}$ O.D. $x 10.0\text{mm}$ Size / Dimension 4.07 " L $x 1.65$ " W $x 1.13$ " H (103.4mm $x 42.0\text{mm}$ $x 28.7\text{mm}$)	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 2.5A Power (Watts) No Load Power Consumption Negative Center Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 12V 2.5A 30W Negative Center ITE (Commercial) Level V Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm 4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $30W$ No Load Power Consumption $300mW$ (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension 4.07 " L x 1.65 " W x 1.13 " H (103.4 mm x 42.0 mm x 28.7 mm)	Voltage - Output	12V
No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.07^{\circ}\text{L x 1.65^{\circ} W x 1.13^{\circ} H (103.4 \text{mm x } 42.0 \text{mm x } 28.7 \text{mm})}$	Current - Output (Max)	2.5A
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Power (Watts)	30W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.07^{\circ}\text{L} \text{ x } 1.65^{\circ}\text{ W x } 1.13^{\circ}\text{ H } (103.4\text{mm x } 42.0\text{mm x } 28.7\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.07^{\circ}\text{L x 1.65^{\circ}W x 1.13^{\circ}H (103.4\text{mm x }42.0\text{mm x }28.7\text{mm})}$	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.07^{\circ}\text{L x }1.65^{\circ}\text{W x }1.13^{\circ}\text{H }(103.4\text{mm x }42.0\text{mm x }28.7\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Efficiency	Level V
Size / Dimension 4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	4.07" L x 1.65" W x 1.13" H (103.4mm x 42.0mm x 28.7mm)
		Report errors?

PSAC30U-120-R-CNR2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSAC30U-120-R-CNR2 Payment Methods



















PSAC30U-120-R-CNR2 Shipping Methods













If you have any question about PSAC30U-120-R-CNR2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com