

PSAC45W-120 Information



For Reference Only

Part Number PSAC45W-120 **Manufacturer** Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 45W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSAC45W-120 Specifications

Manufacturer Part Number PSAC45W-120 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSA45 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 89 ~ 270 VAC Voltage - Output 12V Current - Output (Max) 3.75A Power (Watts) 45W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.72" L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSA45 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 89 ~ 270 VAC Voltage - Output 12V Current - Output (Max) 3.75A Power (Watts) 45W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.72" L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm)	Manufacturer Part Number	PSAC45W-120
AC DC Desktop, Wall Adapters Package - Series PSA45 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 89 ~ 270 VAC Voltage - Output 12V Current - Output (Max) 3.75A Power (Watts) 45W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension A C DC Desktop, Wall Adapters PSA45 POSA45 POSA45 International Positive Center Applications ITE (Commercial) Size / Dimension AC DC Desktop, Wall Adapters PSA45 POSA45 PSA45 International PSA	Manufacturer	Phihong USA
Package - Series PSA45 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 89 ~ 270 VAC Voltage - Output 12V Current - Output (Max) 3.75A Power (Watts) 45W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.72" L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSA45Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input89 ~ 270 VACVoltage - Output12VCurrent - Output (Max)3.75APower (Watts)45WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension4.72" L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 89 ~ 270 VAC Voltage - Output 12V Current - Output (Max) 3.75A Power (Watts) 45W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.72" L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 89 ~ 270 VAC Voltage - Output 12V Current - Output (Max) 3.75A Power (Watts) 45W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.72" L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm)	Series	PSA45
Input Type Cord (Sold Separately) Voltage - Input 89 ~ 270 VAC Voltage - Output 12V Current - Output (Max) 3.75A Power (Watts) 45W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.72" L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm)	Region Utilized	International
Voltage - Input Voltage - Output 12V Current - Output (Max) 3.75A Power (Watts) No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm 4.72" L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm)	Form	Desktop (Class II)
Voltage - Output (Max) 3.75A Power (Watts) 45W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.72" L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 3.75A Power (Watts) 45W No Load Power Consumption Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.72" L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm)	Voltage - Input	89 ~ 270 VAC
Power (Watts) A5W No Load Power Consumption Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.72" L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm)	Voltage - Output	12V
No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension 4.72 " L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm)	Current - Output (Max)	3.75A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.72" L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm)	Power (Watts)	45W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.72^{\circ}\text{L} \times 1.98^{\circ}\text{W} \times 1.24^{\circ}\text{H} (120.0\text{mm} \times 50.4\text{mm} \times 31.4\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.72^{\circ}\text{L} \times 1.98^{\circ}\text{W} \times 1.24^{\circ}\text{H} (120.0\text{mm} \times 50.4\text{mm} \times 31.4\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $4.72^{\circ}\text{L} \times 1.98^{\circ}\text{W} \times 1.24^{\circ}\text{H} (120.0\text{mm} \times 50.4\text{mm} \times 31.4\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 4.72" L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm)	Efficiency	Level VI
Size / Dimension 4.72" L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	4.72" L x 1.98" W x 1.24" H (120.0mm x 50.4mm x 31.4mm)
		Report errors

PSAC45W-120 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSAC45W-120 Payment Methods



















PSAC45W-120 Shipping Methods













If you have any question about PSAC45W-120, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com