



Heisener.com

### PSAC60M-120-R-CN1 Information

Part Number PSAC60M-120-R-CN1

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 12V 60W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PSAC60M-120-R-CN1 Specifications

Manufacturer Part Number         PSAC60M-120-R-CN1           Manufacturer         Phihong USA           Category         Power Supplies - External/Internal (Off-Board)           Reckage         -           Series         PSAC60M           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         5A           Power (Watts)         60W           No Load Power Consumption         500mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm           Size / Dimension         5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesPSAC60MRegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)5APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Manufacturer Part Number	PSAC60M-120-R-CN1
Package         -           Series         PSAC60M           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         5A           Power (Watts)         60W           No Load Power Consumption         500mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm           Size / Dimension         5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Manufacturer	Phihong USA
Package         -           Series         PSAC60M           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         5A           Power (Watts)         60W           No Load Power Consumption         500mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm           Size / Dimension         5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSAC60MRegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)5APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm x 32.0mm) Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 5A  Power (Watts) 60W  No Load Power Consumption 500mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Series	PSAC60M
Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 5A  Power (Watts) 60W  No Load Power Consumption 500mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Region Utilized	International
Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)5APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Form	Desktop (Class I)
Voltage - Output  Current - Output (Max)  5A  Power (Watts)  60W  No Load Power Consumption  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension  12V  12V  12V  12V  12V  12V  12V  12	Input Type	Cord (Sold Separately)
Current - Output (Max)  5A  Power (Watts)  60W  No Load Power Consumption  500mW (Max)  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension  5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 60W  No Load Power Consumption 500mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Voltage - Output	12V
No Load Power Consumption 500mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Current - Output (Max)	5A
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Power (Watts)	60W
Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0\text{mm} \times 60.0\text{mm} \times 32.0\text{mm})$	No Load Power Consumption	500mW (Max)
Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension $5.12^{\circ}\text{L} \text{ x } 2.36^{\circ}\text{ W x } 1.30^{\circ}\text{H} (130.0\text{mm x } 60.0\text{mm x } 32.0\text{mm})$	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0\text{mm} \times 32.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Efficiency	Level VI
Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)
		Report errors?

#### PSAC60M-120-R-CN1 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PSAC60M-120-R-CN1 Payment Methods



















# PSAC60M-120-R-CN1 Shipping Methods













If you have any question about PSAC60M-120-R-CN1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com