



Heisener.com

PSAC60M-560-R-CR5 Information

Part Number PSAC60M-560-R-CR5

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 56V 60W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSAC60M-560-R-CR5 Specifications

Manufacturer Part Number PSAC60M-560-R-CR5 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) Rekage - Series PSAC60M Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 56V Current - Output (Max) 1.08A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm) Report errors?		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesPSAC60MRegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output56VCurrent - Output (Max)1.08APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mmSize / Dimension5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Manufacturer Part Number	PSAC60M-560-R-CR5
Package-SeriesPSAC60MRegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output56VCurrent - Output (Max)1.08APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mmSize / Dimension5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Manufacturer	Phihong USA
Package - Series PSAC60M Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 56V Current - Output (Max) 1.08A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSAC60MRegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output56VCurrent - Output (Max)1.08APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mmSize / Dimension5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 56V Current - Output (Max) 1.08A Power (Watts) 60W No Load Power Consumption 500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm x 32.0mm Size / Dimension 5.12° L x 2.36° W x 1.30° H (130.0mm x 60.0mm x 32.0mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 56V Current - Output (Max) 1.08A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Series	PSAC60M
Input TypeCord (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 56V Current - Output (Max) 1.08A Power (Watts) 60W No Load Power Consumption 500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 5.12° L x 2.36° W x 1.30° H (130.0mm x 60.0mm x 32.0mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 56V Current - Output (Max) 1.08A Power (Watts) 60W No Load Power Consumption 500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 5.12°L x 2.36° W x 1.30° H (130.0mm x 60.0mm x 32.0mm)	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 1.08A Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 56V Current - Output (Max) 1.08A 60W No Load Power Consumption 50mW (Max) Positive Center Level VI Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 1.08A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $60W$ No Load Power Consumption $500mW$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug R/A, $0.7mm$ I.D. x $2.5mm$ O.D. x $10.0mm$ Size / Dimension $5.12"$ L x $2.36"$ W x $1.30"$ H $(130.0mm$ x $60.0mm$ x $32.0mm$)	Voltage - Output	56V
No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Current - Output (Max)	1.08A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0 \text{mm} \times 60.0 \text{mm} \times 32.0 \text{mm})$	Power (Watts)	60W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0° C ~ 40° C Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 5.12° L x 2.36° W x 1.30° H (130.0 mm x 60.0 mm x 32.0 mm)	No Load Power Consumption	500mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0\text{mm} \times 60.0\text{mm} \times 32.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension $5.12^{\circ}\text{L} \text{ x } 2.36^{\circ}\text{W} \text{ x } 1.30^{\circ}\text{H} (130.0\text{mm x } 60.0\text{mm x } 32.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Efficiency	Level VI
Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)
		Report errors?

PSAC60M-560-R-CR5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSAC60M-560-R-CR5 Payment Methods



















PSAC60M-560-R-CR5 Shipping Methods













If you have any question about PSAC60M-560-R-CR5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com