



Heisener.com

PSAC60W-240-R-CN3 Information

Part Number PSAC60W-240-R-CN3

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 24V 60W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSAC60W-240-R-CN3 Specifications

| Manufacturer Part Number PSAC60W-240-R-CN3 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) Rekage - Series PSAC60W Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm) | | |
|---|---------------------------|---|
| CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesPSAC60WRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)2.5APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mmSize / Dimension5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm) | Manufacturer Part Number | PSAC60W-240-R-CN3 |
| Package-SeriesPSAC60WRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)2.5APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mmSize / Dimension5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm) | Manufacturer | Phihong USA |
| Package - Series PSAC60W Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm) | Category | Power Supplies - External/Internal (Off-Board) |
| SeriesPSAC60WRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)2.5APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mmSize / Dimension5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm) | | AC DC Desktop, Wall Adapters |
| Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm x 32.0mm) Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm) | Package | - |
| Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm x 32.0mm) Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm) | Series | PSAC60W |
| Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm) | Region Utilized | International |
| Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 2.5A Power (Watts) 60W No Load Power Consumption 500mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm Size / Dimension 5.12° L x 2.36° W x 1.30° H (130.0mm x 60.0mm x 32.0mm) | Form | Desktop (Class II) |
| Voltage - Output Current - Output (Max) 2.5A Power (Watts) No Load Power Consumption Somw (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm Size / Dimension Size / Dimension 24V 24V 24V 24V 25A 60W No Load Power Consumption Somw (Max) Negative Center Level VI Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm Size / Dimension | Input Type | Cord (Sold Separately) |
| Current - Output (Max) 2.5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm) | Voltage - Input | 90 ~ 264 VAC |
| Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm) | Voltage - Output | 24V |
| No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm) | Current - Output (Max) | 2.5A |
| Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0\text{mm} \times 60.0\text{mm} \times 32.0\text{mm})$ | Power (Watts) | 60W |
| Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0\text{mm} \times 60.0\text{mm} \times 32.0\text{mm})$ | No Load Power Consumption | 500mW (Max) |
| Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0\text{mm} \times 60.0\text{mm} \times 32.0\text{mm})$ | Polarization | Negative Center |
| Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0\text{mm} \times 32.0\text{mm})$ | Applications | ITE (Commercial) |
| Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm) | Efficiency | Level VI |
| Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm) | Operating Temperature | 0°C ~ 40°C |
| | Output Connector | Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 10.0mm |
| Report errors? | Size / Dimension | 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm) |
| | | Report errors? |

PSAC60W-240-R-CN3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSAC60W-240-R-CN3 Payment Methods



















PSAC60W-240-R-CN3 Shipping Methods













If you have any question about PSAC60W-240-R-CN3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com