



Heisener.com

PSAC60W-480-R-CN1 Information

Part Number PSAC60W-480-R-CN1

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 48V 60W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSAC60W-480-R-CN1 Specifications

Manufacturer Part Number PSAC60W-480-R-CN1 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) Rekage - Series PSAC60W Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 1.25A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSAC60W Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 1.25A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Manufacturer Part Number	PSAC60W-480-R-CN1
Package-SeriesPSAC60WRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output48VCurrent - Output (Max)1.25APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Manufacturer	Phihong USA
Package - Series PSAC60W Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 1.25A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSAC60WRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output48VCurrent - Output (Max)1.25APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 1.25A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm x 32.0mm) Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 1.25A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm x 32.0mm) Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Series	PSAC60W
Input TypeCord (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 48V Current - Output (Max) 1.25A Power (Watts) 60W No Load Power Consumption 500mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.1mm I.D. $x 5.5\text{mm}$ O.D. $x 10.0\text{mm}$ Size / Dimension 5.12° L $x 2.36^{\circ}$ W $x 1.30^{\circ}$ H (130.0mm $x 60.0\text{mm}$ $x 32.0\text{mm}$)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 48V Current - Output (Max) 1.25A Power (Watts) 60W No Load Power Consumption 500mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.1rm I.D. x 5.5rm O.D. x 10.0rm x 32.0rm Size / Dimension 5.12° L x 2.36° W x 1.30° H (130.0rm x 60.0rm x 32.0rm)	Form	Desktop (Class II)
Voltage - Output 48V Current - Output (Max) 1.25A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 1.25A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $60W$ No Load Power Consumption $500mW$ (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug, $2.1mm$ I.D. x $5.5mm$ O.D. x $10.0mm$ Size / Dimension $5.12"$ L x $2.36"$ W x $1.30"$ H $(130.0mm$ x $60.0mm$ x $32.0mm$)	Voltage - Output	48V
No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Current - Output (Max)	1.25A
Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0 \text{mm} \times 60.0 \text{mm} \times 32.0 \text{mm})$	Power (Watts)	60W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0\text{mm} \times 60.0\text{mm} \times 32.0\text{mm})$	No Load Power Consumption	500mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0\text{mm} \times 60.0\text{mm} \times 32.0\text{mm})$	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $5.12^{\circ}\text{L} \text{ x } 2.36^{\circ}\text{W} \text{ x } 1.30^{\circ}\text{H} (130.0\text{mm x } 60.0\text{mm x } 32.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Efficiency	Level VI
Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)
		Report errors?

PSAC60W-480-R-CN1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSAC60W-480-R-CN1 Payment Methods



















PSAC60W-480-R-CN1 Shipping Methods













If you have any question about PSAC60W-480-R-CN1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com