

Heisener.com

# PSAC60W-560-R-CNR1

#### PSAC60W-560-R-CNR1 Information

Part Number PSAC60W-560-R-CNR1

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 56V 60W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### PSAC60W-560-R-CNR1 Specifications

Manufacturer Part Number         PSAC60W-560-R-CNR1           Manufacturer         Phihong USA           Category         Power Supplies - External/Internal (Off-Board)           Package         -           Series         PSAC60W           Region Utilized         International           Form         Desktop (Class II)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         56V           Current - Output (Max)         1.08A           Power (Watts)         60W           No Load Power Consumption         500mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm           Size / Dimension         5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesPSAC60WRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output56VCurrent - Output (Max)1.08APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Manufacturer Part Number	PSAC60W-560-R-CNR1
Package-SeriesPSAC60WRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output56VCurrent - Output (Max)1.08APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Manufacturer	Phihong USA
Package         -           Series         PSAC60W           Region Utilized         International           Form         Desktop (Class II)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         56V           Current - Output (Max)         1.08A           Power (Watts)         60W           No Load Power Consumption         500mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm           Size / Dimension         5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSAC60WRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output56VCurrent - Output (Max)1.08APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 56V Current - Output (Max) 1.08A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 56V Current - Output (Max) 1.08A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Series	PSAC60W
Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 56V  Current - Output (Max) 1.08A  Power (Watts) 60W  No Load Power Consumption 500mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $56\text{V}$ Current - Output (Max) $1.08\text{A}$ Power (Watts) $60\text{W}$ No Load Power Consumption $500\text{mW}$ (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, $2.1\text{mm}$ I.D. $x = 5.5\text{mm}$ O.D. $x = 10.0\text{mm}$ Size / Dimension $5.12^{\circ}\text{ L} \times 2.36^{\circ}\text{ W} \times 1.30^{\circ}\text{ H} (130.0\text{mm} \times 32.0\text{mm})$	Form	Desktop (Class II)
Voltage - Output  Current - Output (Max)  1.08A  Power (Watts)  No Load Power Consumption  Polarization  Applications  ITE (Commercial)  Efficiency  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension  56V  Current - Output (Max)  1.08A  60W  Negative Center  ITE (Commercial)  Level VI  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max)  1.08A  Power (Watts)  60W  No Load Power Consumption  500mW (Max)  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension  5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $60W$ No Load Power Consumption $500mW$ (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug R/A, $2.1mm$ I.D. $x$ $5.5mm$ O.D. $x$ $10.0mm$ Size / Dimension $5.12"$ L $x$ $2.36"$ W $x$ $1.30"$ H $(130.0mm$ $x$ $60.0mm$ $x$ $32.0mm$ )	Voltage - Output	56V
No Load Power Consumption 500mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Current - Output (Max)	1.08A
Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0 \text{mm} \times 60.0 \text{mm} \times 32.0 \text{mm})$	Power (Watts)	60W
Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0\text{mm} \times 60.0\text{mm} \times 32.0\text{mm})$	No Load Power Consumption	500mW (Max)
Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm  Size / Dimension $5.12^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.30^{\circ}\text{H} (130.0\text{mm} \times 60.0\text{mm} \times 32.0\text{mm})$	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $5.12^{\circ}\text{L} \text{ x } 2.36^{\circ}\text{W} \text{ x } 1.30^{\circ}\text{H} (130.0\text{mm x } 60.0\text{mm x } 32.0\text{mm})$	Applications	ITE (Commercial)
Output Connector         Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm           Size / Dimension         5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Efficiency	Level VI
Size / Dimension 5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	5.12" L x 2.36" W x 1.30" H (130.0mm x 60.0mm x 32.0mm)
		Report errors?

#### PSAC60W-560-R-CNR1 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PSAC60W-560-R-CNR1 Payment Methods



















# PSAC60W-560-R-CNR1 Shipping Methods













If you have any question about PSAC60W-560-R-CNR1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com