



PSB155-7IR Information

Heisener.com

Part Number PSB155-7IR

Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description DC/DC CONVERT 15V 5A

Package Module

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSB155-7IR Specifications

Manufacturer Part Number PSB155-7IR Manufacturer Bel Power Solutions Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series Melcher PSB Type Non-Isolated Voltage - Input (Min) 19V Voltage - Input (Max) 80V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 92.5% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.17" L x 1.27" W x 2.72" H (106.0mm x 32.2mm x 69.0mm)	•	
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series Melcher PSB Type Non-Isolated Voltage - Input (Min) 19V Voltage - Input (Max) 80V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 92.5% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.17" L x 1.27" W x 2.72" H (106.0mm x 32.2mm x 69.0mm)	Manufacturer Part Number	PSB155-7IR
Package Module Series Melcher PSB Type Non-Isolated Voltage - Input (Min) 19V Voltage - Input (Max) 80V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 92.5% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.17" L x 1.27" W x 2.72" H (106.0mm x 32.2mm x 69.0mm)	Manufacturer	Bel Power Solutions
Package Module Series Melcher PSB Type Non-Isolated Voltage - Input (Min) 19V Voltage - Input (Max) 80V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 92.5% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.17" L x 1.27" W x 2.72" H (106.0mm x 32.2mm x 69.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series Melcher PSB Type Non-Isolated Voltage - Input (Min) 19V Voltage - Input (Max) 80V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 92.5% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.17" L x 1.27" W x 2.72" H (106.0mm x 32.2mm x 69.0mm)		DC DC Converters
Type Non-Isolated Voltage - Input (Min) 19V Voltage - Input (Max) 80V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 92.5% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.17" L x 1.27" W x 2.72" H (106.0mm x 32.2mm x 69.0mm)	Package	Module
Voltage - Input (Min) 19V Voltage - Input (Max) 80V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 92.5% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.17" L x 1.27" W x 2.72" H (106.0mm x 32.2mm x 69.0mm)	Series	Melcher PSB
Voltage - Input (Max) 80V Number of Outputs 1 Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 92.5% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.17" L x 1.27" W x 2.72" H (106.0mm x 32.2mm x 69.0mm)	Туре	Non-Isolated
Number of Outputs Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency Mounting Type Chassis Mount Package / Case Module Size / Dimension 15V	Voltage - Input (Min)	19V
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Applications ITE (Commercial), Railway Operating Temperature Efficiency Mounting Type Chassis Mount Package / Case Size / Dimension 15V	Voltage - Input (Max)	80V
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Railway Operating Temperature Efficiency 92.5% Mounting Type Chassis Mount Package / Case Size / Dimension - Control of the control of	Number of Outputs	1
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 92.5% Mounting Type Chassis Mount Package / Case Module Size / Dimension	Voltage - Output 1	15V
Voltage - Output 4 Current - Output (Max) 5A Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 92.5% Mounting Type Chassis Mount Package / Case Module Size / Dimension	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 92.5% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5A 75W Commercial), Railway -25°C ~ 71°C Chassis Mount 105	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 92.5% Mounting Type Chassis Mount Package / Case Module Size / Dimension 75W Commercial), Railway -25°C ~ 71°C Chassis Mount 1000	Voltage - Output 4	-
Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 92.5% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.17" L x 1.27" W x 2.72" H (106.0mm x 32.2mm x 69.0mm)	Current - Output (Max)	5A
Operating Temperature -25°C ~ 71°C Efficiency 92.5% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.17" L x 1.27" W x 2.72" H (106.0mm x 32.2mm x 69.0mm)	Power (Watts)	75W
Efficiency 92.5% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.17" L x 1.27" W x 2.72" H (106.0mm x 32.2mm x 69.0mm)	Applications	ITE (Commercial), Railway
Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.17" L x 1.27" W x 2.72" H (106.0mm x 32.2mm x 69.0mm)	Operating Temperature	-25°C ~ 71°C
Package / Case Module Size / Dimension 4.17" L x 1.27" W x 2.72" H (106.0mm x 32.2mm x 69.0mm)	Efficiency	92.5%
Size / Dimension 4.17" L x 1.27" W x 2.72" H (106.0mm x 32.2mm x 69.0mm)	Mounting Type	Chassis Mount
	Package / Case	
Report errors?	Size / Dimension	4.17" L x 1.27" W x 2.72" H (106.0mm x 32.2mm x 69.0mm)
		Report errors?

PSB155-7IR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSB155-7IR Payment Methods



















PSB155-7IR Shipping Methods













If you have any question about PSB155-7IR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com