

PSC03R-050 Information



For Reference Only

Part Number PSC03R-050 Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 5V 3W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSC03R-050 Specifications

Manufacturer Part Number PSC03R-050 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSC03R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 500mA Power (Watts) 2.5W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector USB A Receptacle Size / Dimension 2.97" L x 1.81" W x 1.25" H (75.3mm x 46.0mm x 31.7mm)		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesPSC03RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)500mAPower (Watts)2.5WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel IVOperating Temperature0°C ~ 45°COutput ConnectorUSB A Receptacle	Manufacturer Part Number	PSC03R-050
Package-SeriesPSC03RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)500mAPower (Watts)2.5WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel IVOperating Temperature0°C ~ 45°COutput ConnectorUSB A Receptacle	Manufacturer	Phihong USA
Package-SeriesPSC03RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)500mAPower (Watts)2.5WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel IVOperating Temperature0°C ~ 45°COutput ConnectorUSB A Receptacle	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSC03RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)500mAPower (Watts)2.5WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel IVOperating Temperature0°C ~ 45°COutput ConnectorUSB A Receptacle		AC DC Desktop, Wall Adapters
Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 500mA Power (Watts) 2.5W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector USB A Receptacle	Package	-
Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 500mA Power (Watts) 2.5W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector USB A Receptacle	Series	PSC03R
Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 500mA Power (Watts) 2.5W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector USB A Receptacle	Region Utilized	International
Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)500mAPower (Watts)2.5WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel IVOperating Temperature0°C ~ 45°COutput ConnectorUSB A Receptacle	Form	Wall Mount
Voltage - Output (Max) 500mA Power (Watts) 2.5W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector USB A Receptacle	Input Type	Multi-Blade (Sold Separately)
Current - Output (Max) 500mA Power (Watts) 2.5W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector USB A Receptacle	Voltage - Input	90 ~ 264 VAC
Power (Watts) No Load Power Consumption 300mW (Max) Polarization Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector USB A Receptacle	Voltage - Output	5V
No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector USB A Receptacle	Current - Output (Max)	500mA
Polarization - Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector USB A Receptacle	Power (Watts)	2.5W
ApplicationsITE (Commercial)EfficiencyLevel IVOperating Temperature 0° C ~ 45° COutput ConnectorUSB A Receptacle	No Load Power Consumption	300mW (Max)
Efficiency Level IV Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector USB A Receptacle	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector USB A Receptacle	Applications	ITE (Commercial)
Output Connector USB A Receptacle	Efficiency	Level IV
	Operating Temperature	0°C ~ 45°C
Size / Dimension 2.97" L x 1.81" W x 1.25" H (75.3mm x 46.0mm x 31.7mm)	Output Connector	USB A Receptacle
	Size / Dimension	2.97" L x 1.81" W x 1.25" H (75.3mm x 46.0mm x 31.7mm)
Report errors?		Report errors?

PSC03R-050 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSC03R-050 Payment Methods



















PSC03R-050 Shipping Methods













If you have any question about PSC03R-050, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com