

PSC126-7IR Information

Heisener.com

Part Number PSC126-7IR

Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description DC/DC CONVERT 12V 6A

Package Module

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSC126-7IR Specifications

SeriesMelcher PSCTypeNon-IsolatedVoltage - Input (Min)18VVoltage - Input (Max)144VNumber of Outputs1Voltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)6APower (Watts)72WApplicationsITE (Commercial)Operating Temperature-25°C ~ 71°CEfficiency89%Mounting TypeChassis Mount			
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series Melcher PSC Type Non-Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 72W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 89% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Manufacturer Part Number	PSC126-7IR	
Package Module Series Melcher PSC Type Non-Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 72W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 89% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Manufacturer	Bel Power Solutions	
Package Module Series Melcher PSC Type Non-Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 72W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 89% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series Melcher PSC Type Non-Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 72W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 89% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)		DC DC Converters	
Type Non-Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 72W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 89% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Package	Module	
Voltage - Input (Min) 18V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 72W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 89% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Series	Melcher PSC	
Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 72W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 89% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Type	Non-Isolated	
Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 72W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 89% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Voltage - Input (Min)	18V	
Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 72W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 89% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Voltage - Input (Max)	144V	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 89% Mounting Type Chassis Mount Package / Case Size / Dimension - - - - - - - - - - - - -	Number of Outputs	1	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Operating Temperature Efficiency Mounting Type Chassis Mount Package / Case Module Size / Dimension - Current - Output (Max) - CAA APPL x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Voltage - Output 1	12V	
Voltage - Output 4 Current - Output (Max) 6A Power (Watts) Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 89% Mounting Type Chassis Mount Package / Case Module Size / Dimension	Voltage - Output 2	-	
Current - Output (Max) 6A Power (Watts) 72W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 89% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Voltage - Output 3	-	
Power (Watts) 72W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 89% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Voltage - Output 4	-	
Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 89% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Current - Output (Max)	6A	
Operating Temperature -25°C ~ 71°C Efficiency 89% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Power (Watts)	72W	
Efficiency 89% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Applications	ITE (Commercial)	
Mounting Type Chassis Mount Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Operating Temperature	-25°C ~ 71°C	
Package / Case Module Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Efficiency	89%	
Size / Dimension 5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	Mounting Type	Chassis Mount	
	Package / Case	Module	
Report errors?	Size / Dimension	5.94" L x 1.27" W x 3.46" H (151.0mm x 32.2mm x 88.0mm)	
		R	eport errors?

PSC126-7IR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSC126-7IR Payment Methods



















PSC126-7IR Shipping Methods













If you have any question about PSC126-7IR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com