



PSC12R-050-R-CN4 Information

Heisener.com

Part Number PSC12R-050-R-CN4

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 5V 10W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSC12R-050-R-CN4 Specifications

Manufacturer Part Number PSC12R-050-R-CN4 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSC12R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSC12R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)	Manufacturer Part Number	PSC12R-050-R-CN4
AC DC Desktop, Wall Adapters Package - Series PSC12R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)	Manufacturer	Phihong USA
Package - Series PSC12R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSC12RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)2APower (Watts)10WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mmSize / Dimension2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)	Package	-
Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)	Series	PSC12R
Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)	Region Utilized	International
Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)	Form	Wall Mount
Voltage - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)	Input Type	Multi-Blade (Sold Separately)
Current - Output (Max) Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)	Voltage - Output	5V
No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)	Current - Output (Max)	2A
PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mmSize / Dimension 2.82 " L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)	Power (Watts)	10W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension $2.82^{\circ}\text{L} \times 1.77^{\circ}\text{W} \times 1.30^{\circ}\text{H} (71.7\text{mm} \times 45.0\text{mm} \times 33.0\text{mm})$	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension $2.82^{\circ}\text{L} \times 1.77^{\circ}\text{W} \times 1.30^{\circ}\text{H} (71.7\text{mm} \times 45.0\text{mm} \times 33.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)	Efficiency	Level V
Size / Dimension 2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	2.82" L x 1.77" W x 1.30" H (71.7mm x 45.0mm x 33.0mm)
		Report errors?

PSC12R-050-R-CN4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSC12R-050-R-CN4 Payment Methods



















PSC12R-050-R-CN4 Shipping Methods













If you have any question about PSC12R-050-R-CN4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com