

PSC12S-090 Information



For Reference Only

Part Number PSC12S-090 Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 9V 10W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSC12S-090 Specifications

Manufacturer Part Number PSC12S-090 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSC12x Region Utilized Australia Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 1.11A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.82" L x 1.77" W x 1.93" H (71.7mm x 45.0mm x 49.1mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSC12x Region Utilized Australia Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 1.11A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.82" L x 1.77" W x 1.93" H (71.7mm x 45.0mm x 49.1mm)	Manufacturer Part Number	PSC12S-090
Package - Series PSC12x Region Utilized Australia Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 1.11A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.82" L x 1.77" W x 1.93" H (71.7mm x 45.0mm x 49.1mm)	Manufacturer	Phihong USA
Package - Series PSC12x Region Utilized Australia Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 1.11A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.82" L x 1.77" W x 1.93" H (71.7mm x 45.0mm x 49.1mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSC12xRegion UtilizedAustraliaFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output9VCurrent - Output (Max)1.11APower (Watts)10WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.82" L x 1.77" W x 1.93" H (71.7mm x 45.0mm x 49.1mm)		AC DC Desktop, Wall Adapters
Region Utilized Australia Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output Voltage - Output 111A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension Australia Australi	Package	-
Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 1.11A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.82" L x 1.77" W x 1.93" H (71.7mm x 45.0mm x 49.1mm)	Series	PSC12x
Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 1.11A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.82" L x 1.77" W x 1.93" H (71.7mm x 45.0mm x 49.1mm)	Region Utilized	Australia
Voltage - Input90 ~ 264 VACVoltage - Output9VCurrent - Output (Max)1.11APower (Watts)10WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.82" L x 1.77" W x 1.93" H (71.7mm x 45.0mm x 49.1mm)	Form	Wall Mount
Voltage - Output (Max) 1.11A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.82" L x 1.77" W x 1.93" H (71.7mm x 45.0mm x 49.1mm)	Input Type	Multi-Blade (Sold Separately)
Current - Output (Max) 1.11A Power (Watts) 10W No Load Power Consumption Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 1.11A 1.11A 1.10W 1.00W 1.0	Voltage - Input	90 ~ 264 VAC
Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.82" L x 1.77" W x 1.93" H (71.7mm x 45.0mm x 49.1mm)	Voltage - Output	9V
No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.82" L x 1.77" W x 1.93" H (71.7mm x 45.0mm x 49.1mm)	Current - Output (Max)	1.11A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{mm I.D. x 5.5mm O.D. x 9.5mm}$ Size / Dimension 2.82 " L x 1.77 " W x 1.93 " H $(71.7mm x 45.0mm x 49.1mm)$	Power (Watts)	10W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.82" L x 1.77" W x 1.93" H (71.7mm x 45.0mm x 49.1mm)	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $2.82^{\circ}\text{L} \times 1.77^{\circ}\text{W} \times 1.93^{\circ}\text{H} (71.7\text{mm} \times 45.0\text{mm} \times 49.1\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $2.82^{\circ}\text{L} \times 1.77^{\circ}\text{W} \times 1.93^{\circ}\text{H} (71.7\text{mm} \times 45.0\text{mm} \times 49.1\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.82" L x 1.77" W x 1.93" H (71.7mm x 45.0mm x 49.1mm)	Efficiency	Level V
Size / Dimension 2.82" L x 1.77" W x 1.93" H (71.7mm x 45.0mm x 49.1mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	2.82" L x 1.77" W x 1.93" H (71.7mm x 45.0mm x 49.1mm)
		Report errors?

PSC12S-090 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSC12S-090 Payment Methods



















PSC12S-090 Shipping Methods













If you have any question about PSC12S-090, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com