

PSC20R-180 Information



For Reference Only

Part Number PSC20R-180 Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 18V 20W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSC20R-180 Specifications

Manufacturer Part Number PSC20R-180 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSC20R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.11A Power (Watts) 20W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 3.90" L x 2.50" W x 1.40" H (100.0mm x 63.0mm x 36.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSC20R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.11A Power (Watts) 20W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 3.90" L x 2.50" W x 1.40" H (100.0mm x 63.0mm x 36.0mm)	Manufacturer Part Number	PSC20R-180
Package - Series PSC20R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.11A Power (Watts) 20W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 3.90" L x 2.50" W x 1.40" H (100.0mm x 63.0mm x 36.0mm)	Manufacturer	Phihong USA
Package - Series PSC20R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.11A Power (Watts) 20W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 3.90" L x 2.50" W x 1.40" H (100.0mm x 63.0mm x 36.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSC20RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output18VCurrent - Output (Max)1.11APower (Watts)20WNo Load Power Consumption500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel IVOperating Temperature0°C ~ 45°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension3.90" L x 2.50" W x 1.40" H (100.0mm x 63.0mm x 36.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.11A Power (Watts) 20W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 3.90" L x 2.50" W x 1.40" H (100.0mm x 63.0mm x 36.0mm)	Package	-
Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.11A Power (Watts) 20W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 3.90" L x 2.50" W x 1.40" H (100.0mm x 63.0mm x 36.0mm)	Series	PSC20R
Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.11A Power (Watts) 20W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 3.90" L x 2.50" W x 1.40" H (100.0mm x 63.0mm x 36.0mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 18V Current - Output (Max) 1.11A Power (Watts) 20W No Load Power Consumption 500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel IVOperating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 3.90°L x 2.50° W x 1.40° H $(100.0\text{mm}$ x 63.0mm x 36.0mm)	Form	Wall Mount
Voltage - Output Current - Output (Max) 1.11A Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 18V 1.11A 20W No Load Power Consumption 500mW (Max) Positive Center ITE (Commercial) Level IV Operating Temperature O°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm 3.90" L x 2.50" W x 1.40" H (100.0mm x 63.0mm x 36.0mm)	Input Type	Multi-Blade (Sold Separately)
Current - Output (Max) 1.11A Power (Watts) 20W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 3.90" L x 2.50" W x 1.40" H (100.0mm x 63.0mm x 36.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $20W$ No Load Power Consumption $500mW$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel IVOperating Temperature $0^{\circ}C \sim 45^{\circ}C$ Output ConnectorBarrel Plug, $2.1mm$ I.D. x $5.5mm$ O.D. x $10.0mm$ Size / Dimension 3.90 " L x 2.50 " W x 1.40 " H ($100.0mm$ x $63.0mm$ x $36.0mm$)	Voltage - Output	18V
No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level IV Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 3.90" L x 2.50" W x 1.40" H (100.0mm x 63.0mm x 36.0mm)	Current - Output (Max)	1.11A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level IV Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, $2.1 \text{mm I.D. x } 5.5 \text{mm O.D. x } 10.0 \text{mm}$ Size / Dimension $3.90^{\circ}\text{L x } 2.50^{\circ}\text{W x } 1.40^{\circ}\text{H } (100.0 \text{mm x } 63.0 \text{mm x } 36.0 \text{mm})$	Power (Watts)	20W
Applications ITE (Commercial) Efficiency Level IV Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $3.90^{\circ}\text{L} \times 2.50^{\circ}\text{W} \times 1.40^{\circ}\text{H} (100.0 \text{mm} \times 63.0 \text{mm} \times 36.0 \text{mm})$	No Load Power Consumption	500mW (Max)
Efficiency Level IV Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, $2.1 \text{mm I.D. x } 5.5 \text{mm O.D. x } 10.0 \text{mm}$ Size / Dimension $3.90^{\circ}\text{L x } 2.50^{\circ}\text{W x } 1.40^{\circ}\text{H } (100.0 \text{mm x } 63.0 \text{mm x } 36.0 \text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $3.90^{\circ}\text{L x }2.50^{\circ}\text{W x }1.40^{\circ}\text{H }(100.0\text{mm x }63.0\text{mm x }36.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 3.90" L x 2.50" W x 1.40" H (100.0mm x 63.0mm x 36.0mm)	Efficiency	Level IV
Size / Dimension 3.90" L x 2.50" W x 1.40" H (100.0mm x 63.0mm x 36.0mm)	Operating Temperature	0°C ~ 45°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	3.90" L x 2.50" W x 1.40" H (100.0mm x 63.0mm x 36.0mm)
		Report errors?

PSC20R-180 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSC20R-180 Payment Methods



















PSC20R-180 Shipping Methods













If you have any question about PSC20R-180, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com