



PSC75U-560-R-CR1 Information

Heisener.com

Part Number PSC75U-560-R-CR1

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 56V 75W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSC75U-560-R-CR1 Specifications

Manufacturer Part Number PSC75U-560-R-CR1 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) Rekage - Series PSC75U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 56V Current - Output (Max) 1.34A Power (Watts) 75W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.93" L x 2.78" W x 1.54" H (150.5mm x 70.5mm x 39.0mm)		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesPSC75URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output56VCurrent - Output (Max)1.34APower (Watts)75WNo Load Power Consumption500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension5.93" L x 2.78" W x 1.54" H (150.5mm x 70.5mm x 39.0mm)	Manufacturer Part Number	PSC75U-560-R-CR1
Package-SeriesPSC75URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output56VCurrent - Output (Max)1.34APower (Watts)75WNo Load Power Consumption500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension5.93" L x 2.78" W x 1.54" H (150.5mm x 70.5mm x 39.0mm)	Manufacturer	Phihong USA
Package - Series PSC75U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 56V Current - Output (Max) 1.34A Power (Watts) 75W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.93" L x 2.78" W x 1.54" H (150.5mm x 70.5mm x 39.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSC75URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output56VCurrent - Output (Max)1.34APower (Watts)75WNo Load Power Consumption500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension5.93" L x 2.78" W x 1.54" H (150.5mm x 70.5mm x 39.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 56V Current - Output (Max) 1.34A Power (Watts) 75W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.93" L x 2.78" W x 1.54" H (150.5mm x 70.5mm x 39.0mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 56V Current - Output (Max) 1.34A Power (Watts) 75W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.93" L x 2.78" W x 1.54" H (150.5mm x 70.5mm x 39.0mm)	Series	PSC75U
Input TypeCord (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 56V Current - Output (Max) 1.34A Power (Watts) 75W No Load Power Consumption 500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.93° L x 2.78° W x 1.54° H (150.5mm x 70.5mm x 39.0mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 56V Current - Output (Max) 1.34A Power (Watts) 75W No Load Power Consumption 500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.1mm I.D. $x = 5.5\text{mm}$ O.D. $x = 10.0\text{mm}$ Size / Dimension $5.93^{\circ}\text{L} \times 2.78^{\circ}\text{W} \times 1.54^{\circ}\text{H} (150.5\text{mm} \times 70.5\text{mm} \times 39.0\text{mm})$	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 1.34A Power (Watts) No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 56V Current - Output (Max) 1.34A 75W No Load Power Consumption 500mW (Max) Positive Center ITE (Commercial) Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm 5.93" L x 2.78" W x 1.54" H (150.5mm x 70.5mm x 39.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 1.34A Power (Watts) 75W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.93" L x 2.78" W x 1.54" H (150.5mm x 70.5mm x 39.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $75W$ No Load Power Consumption $500mW$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug R/A, $2.1mm$ I.D. x $5.5mm$ O.D. x $10.0mm$ Size / Dimension 5.93 " L x 2.78 " W x 1.54 " H ($150.5mm$ x $70.5mm$ x $39.0mm$)	Voltage - Output	56V
No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.93" L x 2.78" W x 1.54" H (150.5mm x 70.5mm x 39.0mm)	Current - Output (Max)	1.34A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.93" L x 2.78" W x 1.54" H (150.5mm x 70.5mm x 39.0mm)	Power (Watts)	75W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0° C ~ 40° C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.93" L x 2.78" W x 1.54" H (150.5mm x 70.5mm x 39.0mm)	No Load Power Consumption	500mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $5.93^{\circ}\text{L} \times 2.78^{\circ}\text{W} \times 1.54^{\circ}\text{H} (150.5\text{mm} \times 70.5\text{mm} \times 39.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $5.93^{\circ}\text{L} \times 2.78^{\circ}\text{W} \times 1.54^{\circ}\text{H} (150.5\text{mm} \times 70.5\text{mm} \times 39.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 5.93" L x 2.78" W x 1.54" H (150.5mm x 70.5mm x 39.0mm)	Efficiency	Level VI
Size / Dimension 5.93" L x 2.78" W x 1.54" H (150.5mm x 70.5mm x 39.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	5.93" L x 2.78" W x 1.54" H (150.5mm x 70.5mm x 39.0mm)
		Report errors?

PSC75U-560-R-CR1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSC75U-560-R-CR1 Payment Methods



















PSC75U-560-R-CR1 Shipping Methods













If you have any question about PSC75U-560-R-CR1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com