

PSK1212-7

PSK1212-7 Information

Heisener.com	 PSK1212-7 Bel Power Solutions Power Supplies - External/Internal (Off-Board) DC DC Converters DC/DC CONVERT 12V 12A Module For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PSK1212-7 Specifications

ManufacturerBel Power SolutionsCategoryPower Supplies - External/Internal (Off-Board)DC DC ConvertersPackageModuleSeriesMelcher PSKTypeNon-IsolatedVoltage - Input (Min)18VVoltage - Input (Max)144VNumber of Outputs1Voltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 412APower (Watts)144WApplications144WOperating Temperature23°C ~ 71°CPower (Watts)91%Mounting TypeChasis MountPackage / CaseModuleSize / Dimension673°L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)				
CategoryPower Supplies - External/Internal (Off-Board)DC DC ConvertersPackageModuleSeriesMelcher PSKTypeNon-IsolatedVoltage - Input (Min)18VVoltage - Input (Max)144VNumber of Outputs1Voltage - Output 112VVoltage - Output 2-Voltage - Output 4-Voltage - Output 4-Voltage - Output 412AVoltage - Output 4-Voltage - Output 4-Power (Watts)144WApplicationsTE (Commercial)Operating Temperature-25°C ~ 71°CEfficiency91%Mounting TypeChasis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Manufacturer Part Number	PSK1212-7		
DC DC ConvertersPackageModuleSeriesMelcher PSKTypeNon-IsolatedVoltage - Input (Min)18VVoltage - Input (Max)144VNumber of Outputs1Voltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12APower (Watts)144WApplicationsITE (Commercial)Operating Temperature-25°C ~71°CEfficiency91%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Manufacturer	Bel Power Solutions		
PackageModuleSeriesMelcher PSKTypeNon-IsolatedVoltage - Input (Min)18VVoltage - Input (Max)144VNumber of Outputs1Voltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Serier 6, Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Serier 6, Output 4-Operating Temperature144WOperating Temperature-25°C ~ 71°CMounting TypeChasis MountPackage / CaseModuleSize / Dimension6.3" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series Melcher PSK Spe Non-Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 144W Applications 144W Operating Temperature -25°C ~ 71°C Efficiency 91% Mounting Type Chasis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)		DC DC Converters		
Type Non-Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Power (Watts) 12A Power (Watts) 144W Applications ITE (commercial) Operating Temperature -25°C ~ 71°C Efficiency 91% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Package	Module		
Voltage - Input (Min) 18V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Wats) 12A Power (Wats) 144W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 91% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Series	Melcher PSK		
Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Wats) 144W Applications 144W Operating Temperature -25°C ~ 71°C Efficiency 91% Mounting Type Chasis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Туре	Non-Isolated		
Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 144W Applications TE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 91% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Voltage - Input (Min)	18V		
Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 144W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 91% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Voltage - Input (Max)	144V		
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12APower (Watts)144WApplicationsITE (Commercial)Operating Temperature-25°C ~ 71°CEfficiency91%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Number of Outputs	1		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12APower (Watts)144WApplicationsITE (Commercial)Operating Temperature-25°C ~ 71°CEfficiency91%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Voltage - Output 1	12V		
Voltage - Output 4-Current - Output (Max)12APower (Watts)144WApplicationsITE (Commercial)Operating Temperature-25°C ~ 71°CEfficiency91%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Voltage - Output 2	-		
Current - Output (Max)12APower (Watts)144WApplicationsITE (Commercial)Operating Temperature-25°C ~ 71°CEfficiency91%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Voltage - Output 3	-		
Power (Watts)144WApplicationsITE (Commercial)Operating Temperature-25°C ~ 71°CEfficiency91%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 52.2mm)	Voltage - Output 4	-		
ApplicationsITE (Commercial)Operating Temperature-25°C ~ 71°CEfficiency91%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Current - Output (Max)	12A		
Operating Temperature-25°C ~ 71°CEfficiency91%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Power (Watts)	144W		
Efficiency91%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Applications	ITE (Commercial)		
Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Operating Temperature	-25°C ~ 71°C		
Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Efficiency	91%		
Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Mounting Type	Chassis Mount		
	Package / Case	Module		
Report errors	Size / Dimension	6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)		
			Report errors?	

PSK1212-7 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about PSK1212-7, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com