

PSK3612-7

PSK3612-7 Information

	Contact service starts they	 PSK3612-7 Bel Power Solutions Power Supplies - External/Internal (Off-Board) DC DC Converters DC/DC CONVERT 36V 12A Module For the pricing/inventory/lead time, please contact	
	For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PSK3612-7 Specifications

ManufacturerBel Power SolutionsCategoryPower Supplies - External/Internal (Off-Board)DC DC ConvertersPackageModuleSeriesMelcher PSKTypeNon-IsolatedVoltage - Input (Min)44VVoltage - Input (Max)144VNumber of Outputs1Voltage - Output 136VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Series32WOutrent - Output (Max)12APower (Watts)432WApplications15C ° ~ 71 °COprating Temperature6%Mounting Type6xasis MountPackage / CaseModuleSiz / Dimension6.73 ° L x 4.37 ° W x 2.06 ° H (171.0mm x 111.0mm x 52.2mm)				
CategoryPower Supplies - External/Internal (Off-Board)DC DC ConvertersPackageModuleSeriesMelcher PSKTypeNon-IsolatedVoltage - Input (Min)44VVoltage - Input (Max)144VNumber of Outputs1Voltage - Output 136VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Power (Watts)12AApplicationsTE (Commercial)Operating Temperature6%Fiftiency96%Mounting TypeKasis MountPackage / CaseModuleSiz / Dimension6.73" L x 4.37" W x 2.06" H (17.10mm x 11.0mm x 52.2mm)	Manufacturer Part Number	PSK3612-7		
DC DC Converters Package Module Series Melcher PSK Type Non-Isolated Voltage - Input (Min) 44V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Power (Wats) 432W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Manufacturer	Bel Power Solutions		
PackageModuleSeriesMelcher PSKTypeNon-IsolatedVoltage - Input (Min)44VVoltage - Input (Max)144VNumber of Outputs1Voltage - Output 136VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Power (Watts)12AApplicationsTE (Commercial)Operating Temperature96%Mounting TypeGuasis MountPackage / CaseModuleSiz / Dimension5.3" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series Melcher PSK Type Non-Isolated Voltage - Input (Min) 44V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Power (Watts) 12A Applications ITE (Commercial) Operating Temperature 6% Mounting Type Gensis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)		DC DC Converters		
Type Non-Isolated Voltage - Input (Min) 44V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Power (Watts) 12A Power (Watts) 432W Operating Temperature -25°C ~ 71°C Operating Temperature 6% Mounting Type Module Package / Case Module Size / Dinension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Package	Module		
Voltage - Input (Min) 44V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Power (Watts) 12A Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Pakage / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Series	Melcher PSK		
Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 432W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chasis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Туре	Non-Isolated		
Number of Outputs 1 Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 432W Applications TE (Commercial) Operating Temperature -5°C ~ 71°C Efficiency 96% Mounting Type Chasis Mount Package / Case Module Size / Dimension 6.3" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Voltage - Input (Min)	44V		
Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 432W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chasis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Voltage - Input (Max)	144V		
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 432W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Number of Outputs	1		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12APower (Watts)432WApplicationsITE (Commercial)Operating Temperature-25°C ~ 71°CEfficiency96%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 51.2mm)	Voltage - Output 1	36V		
Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 432W Applications ITE (commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Voltage - Output 2	-		
Current - Output (Max)12APower (Watts)432WApplicationsITE (Commercial)Operating Temperature-25°C ~ 71°CEfficiency96%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Voltage - Output 3	-		
Power (Watts)432WApplicationsITE (Commercial)Operating Temperature-25°C ~ 71°CEfficiency96%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 52.2mm)	Voltage - Output 4	-		
ApplicationsITE (Commercial)Operating Temperature-25°C ~ 71°CEfficiency96%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Current - Output (Max)	12A		
Operating Temperature-25°C ~ 71°CEfficiency96%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Power (Watts)	432W		
Efficiency96%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Applications	ITE (Commercial)		
Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Operating Temperature	-25°C ~ 71°C		
Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Efficiency	96%		
Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Mounting Type	Chassis Mount		
	Package / Case	Module		
Report errors	Size / Dimension	6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)		
			Report errors?	

PSK3612-7 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about PSK3612-7, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com