

PSL366-7R Information

Heisener.com

Part Number PSL366-7R

Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description SWITCHING REGULATOR 216W 36V

Package Module

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSL366-7R Specifications

Manufacturer Part Number PSL366-7R Manufacturer Bel Power Solutions Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series Melcher PSL Type Non-Isolated Voltage - Input (Min) 44V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 216W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm) Report errors?			
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series Melcher PSL Type Non-Isolated Voltage - Input (Min) 44V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 216W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm)	Manufacturer Part Number	PSL366-7R	
Package Module Series Melcher PSL Type Non-Isolated Voltage - Input (Min) 44V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 216W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm)	Manufacturer	Bel Power Solutions	
Package Module Series Melcher PSL Type Non-Isolated Voltage - Input (Min) 44V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 216W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series Melcher PSL Type Non-Isolated Voltage - Input (Min) 44V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 216W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm)		DC DC Converters	
Type Non-Isolated Voltage - Input (Min) 44V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 216W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm)	Package	Module	
Voltage - Input (Min) 44V Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 216W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm)	Series	Melcher PSL	
Voltage - Input (Max) 144V Number of Outputs 1 Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 216W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm)	Type	Non-Isolated	
Number of Outputs 1 Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6A Power (Watts) 216W Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm)	Voltage - Input (Min)	44V	
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Operating Temperature Efficiency Mounting Type Chassis Mount Package / Case Module Size / Dimension 36V - 36V	Voltage - Input (Max)	144V	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension - Company - C	Number of Outputs	1	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Operating Temperature Efficiency Mounting Type Chassis Mount Package / Case Module Size / Dimension - Output (Max) - CA APPLICATION FACTOR CHASSIS MOUNT APPLICATION CHASSIS MOUNT APPLICATION - CA APPLICATION CHASSIS MOUNT APPLICATION APPLICATION APPLICATION APPLICATION APPLICATION - CA APPLICATION - CA APPLICATION - CA	Voltage - Output 1	36V	
Voltage - Output 4 Current - Output (Max) 6A Power (Watts) Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension - Output (Max) - Chassis Mount - Commercial) - Chassis Mount - Chassis	Voltage - Output 2	-	
Current - Output (Max) Power (Watts) Applications Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6A 216W Commercial -25°C ~ 71°C Chassis Mount (Chassis	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 216W Commercial) -25°C ~ 71°C Chassis Mount Chassis Mount Mounting Type Chassis Mount Module 6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm)	Voltage - Output 4	-	
Applications ITE (Commercial) Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm)	Current - Output (Max)	6A	
Operating Temperature -25°C ~ 71°C Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension -25°C ~ 71°C Chassis Mount (168.5mm x 107.0mm x 36.5mm)	Power (Watts)	216W	
Efficiency 96% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm)	Applications	ITE (Commercial)	
Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm)	Operating Temperature	-25°C ~ 71°C	
Package / Case Module Size / Dimension 6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm)	Efficiency	96%	
Size / Dimension 6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm)	Mounting Type	Chassis Mount	
	Package / Case	Module	
Report errors?	Size / Dimension	6.63" L x 4.21" W x 1.44" H (168.5mm x 107.0mm x 36.5mm)	
		Report errors	?

PSL366-7R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSL366-7R Payment Methods



















PSL366-7R Shipping Methods













If you have any question about PSL366-7R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com