

PSM03C-050Q-3 Information

Heisener.com

Part Number PSM03C-050Q-3 Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 5V 3W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSM03C-050Q-3 Specifications

Manufacturer Part Number PSM03C-050Q-3 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSM03x Region Utilized China Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 550mA Power (Watts) 2.8W No Load Power Consumption 30mW (Max) Polarization - Applications ITE (Commercial) Efficiency 63.7% Operating Temperature 0°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 0.83" L x 1.69" W x 1.65" H (21.0mm x 43.0mm x 42.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSM03x Region Utilized China Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 550mA Power (Watts) 2.8W No Load Power Consumption 30mW (Max) Polarization - Applications ITE (Commercial) Efficiency 63.7% Operating Temperature 0°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 0.83" L x 1.69" W x 1.65" H (21.0mm x 43.0mm x 42.0mm)	Manufacturer Part Number	PSM03C-050Q-3
AC DC Desktop, Wall Adapters Package - Series PSM03x Region Utilized China Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output SV Current - Output (Max) Power (Watts) SomA Power (Watts) SomA No Load Power Consumption Jomes (Max) Polarization Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Size / Dimension AC DC Desktop, Wall Adapters PSM03x Adapters PSM03x PSM03x Adapters PSM03x Polarization AC DC Desktop, Wall Adapters PSM03x PSM03x Adapters PSM03x Fixed Blade Size / Dimension AC DC Desktop, Wall Adapters PSM03x PSM03x Fixed Blade Size / Dimension AC DC Desktop, Wall Adapters PSM03x PSM03x Fixed Blade Size / Dimension AC DC Desktop, Wall Adapters PSM03x Fixed Blade Size / Dimension AC DC Desktop, Wall Adapters PSM03x Fixed Blade Size / Dimension AC DC Desktop, Wall Adapters PSM03x Fixed Blade Size / Dimension AC DESktop, Wall Adapters PSM03x Fixed Blade Size / Dimension AC Desktop, Wall Adapters PSM03x Fixed Blade F	Manufacturer	Phihong USA
Package - Series PSM03x Region Utilized China Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 550mA Power (Watts) 2.8W No Load Power Consumption 30mW (Max) Polarization - Applications ITE (Commercial) Efficiency 63.7% Operating Temperature 0°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 0.83" L x 1.69" W x 1.65" H (21.0mm x 43.0mm x 42.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series PSM03x Region Utilized China Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 550mA Power (Watts) 2.8W No Load Power Consumption 30mW (Max) Polarization - Applications ITE (Commercial) Efficiency 63.7% Operating Temperature 0°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 0.83" L x 1.69" W x 1.65" H (21.0mm x 43.0mm x 42.0mm)		AC DC Desktop, Wall Adapters
Region Utilized Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 550mA Power (Watts) No Load Power Consumption 30mW (Max) Polarization - Applications ITE (Commercial) Efficiency 63.7% Operating Temperature 0°C ~ 40°C Output Connector Size / Dimension China Wall Mount Fixed Blade 80 ~ 264 VAC VOR 5V Current - Output (Max) 550mA 550mA 70 — 2.8W No Load Power Consumption 30mW (Max) 1TE (Commercial) Efficiency 63.7% Operating Temperature 0°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 0.83" L x 1.69" W x 1.65" H (21.0mm x 43.0mm x 42.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 550mA Power (Watts) 2.8W No Load Power Consumption 30mW (Max) Polarization - Applications ITE (Commercial) Efficiency 63.7% Operating Temperature 0°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 0.83" L x 1.69" W x 1.65" H (21.0mm x 43.0mm x 42.0mm)	Series	PSM03x
Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 550mA Power (Watts) 2.8W No Load Power Consumption 30mW (Max) Polarization - Applications ITE (Commercial) Efficiency 63.7% Operating Temperature 0°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 9.264 VAC	Region Utilized	China
Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 550mA Power (Watts) No Load Power Consumption 30mW (Max) Polarization - Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 90 ~ 264 VAC 5V Current - Output (Max) 50mA 2.8W No Load Power Consumption 30mW (Max) - 40mm cial) 63.7% Operating Temperature 0°C ~ 40°C 0x83" L x 1.69" W x 1.65" H (21.0mm x 43.0mm x 42.0mm)	Form	Wall Mount
Voltage - Output Current - Output (Max) 550mA Power (Watts) 100 Load Power Consumption 200 MW (Max) Polarization Applications Fifficiency 100 C ~ 40°C Output Connector USB A Receptacle Size / Dimension 5V 5V 5V 5V 61 5V 62 84 65 65 65 65 65 65 65 65 65 6	Input Type	Fixed Blade
Current - Output (Max) 550mA Power (Watts) 2.8W No Load Power Consumption 30mW (Max) Polarization - Applications ITE (Commercial) Efficiency 63.7% Operating Temperature 0°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 0.83" L x 1.69" W x 1.65" H (21.0mm x 43.0mm x 42.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 2.8W No Load Power Consumption 30mW (Max) Polarization - Applications ITE (Commercial) Efficiency 63.7% Operating Temperature 0°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 2.8W Omage Omage Oward Oward	Voltage - Output	5V
No Load Power Consumption 30mW (Max) Polarization - Applications ITE (Commercial) Efficiency 63.7% Operating Temperature 0°C ~ 40°C Output Connector USB A Receptacle Size / Dimension 0.83" L x 1.69" W x 1.65" H (21.0mm x 43.0mm x 42.0mm)	Current - Output (Max)	550mA
Polarization - Applications ITE (Commercial) Efficiency 63.7% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector USB A Receptacle Size / Dimension $0.83^{\circ}\text{L} \times 1.69^{\circ}\text{W} \times 1.65^{\circ}\text{H} (21.0 \text{mm} \times 43.0 \text{mm} \times 42.0 \text{mm})$	Power (Watts)	2.8W
Applications ITE (Commercial) Efficiency 63.7% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector USB A Receptacle Size / Dimension $0.83^{\circ}\text{L} \times 1.69^{\circ}\text{W} \times 1.65^{\circ}\text{H} (21.0 \text{mm} \times 43.0 \text{mm} \times 42.0 \text{mm})$	No Load Power Consumption	30mW (Max)
Efficiency 63.7% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector USB A Receptacle Size / Dimension $0.83^{\circ}\text{L x } 1.69^{\circ}\text{W x } 1.65^{\circ}\text{H } (21.0\text{mm x } 43.0\text{mm x } 42.0\text{mm})$	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector USB A Receptacle Size / Dimension $0.83^{\circ}\text{L x } 1.69^{\circ}\text{W x } 1.65^{\circ}\text{H } (21.0\text{mm x } 43.0\text{mm x } 42.0\text{mm})$	Applications	ITE (Commercial)
Output Connector USB A Receptacle Size / Dimension 0.83" L x 1.69" W x 1.65" H (21.0mm x 43.0mm x 42.0mm)	Efficiency	63.7%
Size / Dimension 0.83" L x 1.69" W x 1.65" H (21.0mm x 43.0mm x 42.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	USB A Receptacle
Report errors?	Size / Dimension	0.83" L x 1.69" W x 1.65" H (21.0mm x 43.0mm x 42.0mm)
		Report errors?

PSM03C-050Q-3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSM03C-050Q-3 Payment Methods



















PSM03C-050Q-3 Shipping Methods













If you have any question about PSM03C-050Q-3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com