



## PSM04A-050(STD) Information



For Reference Only

Part Number PSM04A-050(STD)

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 5V 4W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## PSM04A-050(STD) Specifications

Manufacturer Part Number         PSM04A-050(STD)           Manufacturer         Phihong USA           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         PSM04A           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         5V           Current - Output (Max)         750mA           Power (Watts)         3.8W           No Load Power Consumption         500mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level IV           Operating Temperature         0°C ~ 45°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)    Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         PSM04A           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         5V           Current - Output (Max)         750mA           Power (Watts)         3.8W           No Load Power Consumption         500mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level IV           Operating Temperature         0°C ~ 45°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)	Manufacturer Part Number	PSM04A-050(STD)
Package         -           Series         PSM04A           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         5V           Current - Output (Max)         750mA           Power (Watts)         3.8W           No Load Power Consumption         500mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level IV           Operating Temperature         0°C ~ 45°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)	Manufacturer	Phihong USA
Package         -           Series         PSM04A           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         5V           Current - Output (Max)         750mA           Power (Watts)         3.8W           No Load Power Consumption         500mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level IV           Operating Temperature         0°C ~ 45°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSM04ARegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)750mAPower (Watts)3.8WNo Load Power Consumption500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel IVOperating Temperature0°C ~ 45°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $5V$ Current - Output (Max) $750\text{mA}$ Power (Watts) $3.8\text{W}$ No Load Power Consumption $500\text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel IVOperating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{mm}$ I.D. $x$ $5.5\text{mm}$ O.D. $x$ $9.5\text{mm}$ Size / Dimension $2.73^{\circ}$ L $x$ $1.89^{\circ}$ W $x$ $0.98^{\circ}$ H $(69.4\text{mm}$ $x$ $48.0\text{mm}$ $x$ $25.0\text{mm})$	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 750mA Power (Watts) 3.8W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level IV Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)	Series	PSM04A
Input Type Fixed Blade  Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V  Current - Output (Max) 750mA  Power (Watts) 3.8W  No Load Power Consumption 500mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level IV  Operating Temperature 0°C ~ 45°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)	Region Utilized	North America
Voltage - Input  90 ~ 264 VAC  Voltage - Output  5V  Current - Output (Max)  750mA  Power (Watts)  3.8W  No Load Power Consumption  500mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 45°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)	Form	Wall Mount
Voltage - Output (Max) 750mA  Power (Watts) 3.8W  No Load Power Consumption 500mW (Max)  Polarization Positive Center Applications ITE (Commercial)  Efficiency Level IV  Operating Temperature 0°C ~ 45°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)	Input Type	Fixed Blade
Current - Output (Max)  Power (Watts)  3.8W  No Load Power Consumption  500mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level IV  Operating Temperature  0°C ~ 45°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  3.8W  No Load Power Consumption  500mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level IV  Operating Temperature  0°C ~ 45°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)	Voltage - Output	5V
No Load Power Consumption 500mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level IV  Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)	Current - Output (Max)	750mA
Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level IV  Operating Temperature 0°C ~ 45°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)	Power (Watts)	3.8W
Applications ITE (Commercial)  Efficiency Level IV  Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)	No Load Power Consumption	500mW (Max)
Efficiency Level IV  Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $2.73^{\circ}\text{L} \times 1.89^{\circ}\text{W} \times 0.98^{\circ}\text{H} (69.4\text{mm} \times 48.0\text{mm} \times 25.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $2.73^{\circ}\text{L x }1.89^{\circ}\text{W x }0.98^{\circ}\text{H }(69.4\text{mm x }48.0\text{mm x }25.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)	Efficiency	Level IV
Size / Dimension 2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)	Operating Temperature	0°C ~ 45°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	2.73" L x 1.89" W x 0.98" H (69.4mm x 48.0mm x 25.0mm)
		Report errors?

## PSM04A-050(STD) Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PSM04A-050(STD) Payment Methods





















## PSM04A-050(STD) Shipping Methods













If you have any question about PSM04A-050(STD), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com