

PSM090-240P Information



For Reference Only

Part Number PSM090-240P **Manufacturer** Phihong USA

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CV AC/DC 24V 3.75A

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSM090-240P Specifications

Manufacturer Part Number PSM090-240P Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series PSM090-240P Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 304VAC Voltage - Output (Max) 3.75A Power (Watts) 90W Voltage - Isolation 3kV (3000V) Dimming - Features OCP, OTP, OVP, SCP Ratings - Operating Temperature -10°C ~ 40°C Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)			
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series PSM090-240P Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Output (Max) 304VAC Current - Output (Max) 3.75A Power (Watts) 90W Voltage - Isolation 3kV (3000V) Dimming - Features OCP, OTP, OVP, SCP Ratings - Operating Temperature -10°C ~ 40°C Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Manufacturer Part Number	PSM090-240P	
Package - Series PSM090-240P Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 304VAC Voltage - Output 24V Current - Output (Max) 3.75A Power (Watts) 90W Voltage - Isolation 3kV (3000V) Dimming - Features OCP, OTP, OVP, SCP Ratings - Operating Temperature -10°C ~ 40°C Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Manufacturer	Phihong USA	
Package - Series PSM090-240P Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 304VAC Voltage - Output 24V Current - Output (Max) 3.75A Power (Watts) 90W Voltage - Isolation 3kV (3000V) Dimming - Features OCP, OTP, OVP, SCP Ratings - Operating Temperature -10°C ~ 40°C Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series PSM090-240P Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 304VAC Voltage - Output 24V Current - Output (Max) 3.75A Power (Watts) 90W Voltage - Isolation 3kV (3000V) Dimming - Features OCP, OTP, OVP, SCP Ratings - Operating Temperature -10°C ~ 40°C Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)		LED Drivers	
Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90V AC Voltage - Input (Max) 304V AC Voltage - Output 24V Current - Output (Max) 3.75 A Power (Watts) 90W Voltage - Isolation 3kV (3000V) Dimming - Features OCP, OTP, OVP, SCP Ratings - Operating Temperature -10°C ~ 40°C Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Package	-	
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 304VAC Voltage - Output 24V Current - Output (Max) 3.75A Power (Watts) 90W Voltage - Isolation 3kV (3000V) Dimming - Features OCP, OTP, OVP, SCP Ratings - Operating Temperature -10°C ~ 40°C Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Series	PSM090-240P	
Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 304VAC Voltage - Output 24V Current - Output (Max) 3.75A Power (Watts) 90W Voltage - Isolation 3kV (3000V) Dimming - Features OCP, OTP, OVP, SCP Ratings - Operating Temperature -10°C ~ 40°C Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Туре	Constant Voltage	
Voltage - Input (Min)90VACVoltage - Input (Max)304VACVoltage - Output24VCurrent - Output (Max)3.75APower (Watts)90WVoltage - Isolation3kV (3000V)Dimming-FeaturesOCP, OTP, OVP, SCPRatings-Operating Temperature-10°C ~ 40°CEfficiency85%Termination StyleTerminal BlockSize / Dimension6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Topology	AC DC Converter	
Voltage - Input (Max) 304VAC Voltage - Output 24V Current - Output (Max) 3.75A Power (Watts) 90W Voltage - Isolation 3kV (3000V) Dimming - Features OCP, OTP, OVP, SCP Ratings - Operating Temperature -10°C ~ 40°C Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Number of Outputs	1	
Voltage - Output 24V Current - Output (Max) 3.75A Power (Watts) 90W Voltage - Isolation 3kV (3000V) Dimming - Features OCP, OTP, OVP, SCP Ratings - Operating Temperature -10°C ~ 40°C Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Voltage - Input (Min)	90VAC	
Current - Output (Max) 3.75A Power (Watts) 90W Voltage - Isolation 3kV (3000V) Dimming - Features OCP, OTP, OVP, SCP Ratings - Operating Temperature -10°C ~ 40°C Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Voltage - Input (Max)	304VAC	
Power (Watts) 90W Voltage - Isolation 3kV (3000V) Dimming - Features OCP, OTP, OVP, SCP Ratings - Operating Temperature -10°C ~ 40°C Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Voltage - Output	24V	
Voltage - Isolation 3kV (3000V) Dimming - Features OCP, OTP, OVP, SCP Ratings - Operating Temperature -10°C ~ 40°C Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Current - Output (Max)	3.75A	
Dimming - Features OCP, OTP, OVP, SCP Ratings - Operating Temperature -10°C ~ 40°C Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Power (Watts)	90W	
Features OCP, OTP, OVP, SCP Ratings - Operating Temperature -10°C ~ 40°C Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Voltage - Isolation	3kV (3000V)	
Ratings - Operating Temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65° L x 2.40° W x 1.22° H ($169.0 \text{mm} \times 31.0 \text{mm}$)	Dimming	-	
Operating Temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65° L x 2.40° W x 1.22° H ($169.0 \text{mm} \times 61.0 \text{mm} \times 31.0 \text{mm}$)	Features	OCP, OTP, OVP, SCP	
Efficiency 85% Termination Style Terminal Block Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Ratings	-	
Termination Style Size / Dimension Terminal Block 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Operating Temperature	-10°C ~ 40°C	
Size / Dimension 6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	Efficiency	85%	
	Termination Style	Terminal Block	
Report errors?	Size / Dimension	6.65" L x 2.40" W x 1.22" H (169.0mm x 61.0mm x 31.0mm)	
		Report errors?	?

PSM090-240P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSM090-240P Payment Methods

































If you have any question about PSM090-240P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com