



PSM36W-120-TW2 Information



For Reference Only

Part Number PSM36W-120-TW2

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 36W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSM36W-120-TW2 Specifications

Manufacturer Part Number PSM36W-120-TW2 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) Rekage - Series PSM36W Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 89 ~ 270 VAC Voltage - Output 12V Current - Output (Max) 3A Power (Watts) 36W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mm Size / Dimension 4.72" L x 1.98" W x 1.27" H (120.0mm x 50.0mm x 31.5mm)		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesPSM36WRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input89 ~ 270 VACVoltage - Output12VCurrent - Output (Max)3APower (Watts)36WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 45°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mmSize / Dimension4.72" L x 1.98" W x 1.27" H (120.0mm x 50.0mm x 31.5mm)	Manufacturer Part Number	PSM36W-120-TW2
Package-SeriesPSM36WRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input89 ~ 270 VACVoltage - Output12VCurrent - Output (Max)3APower (Watts)36WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 45°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mmSize / Dimension4.72" L x 1.98" W x 1.27" H (120.0mm x 50.0mm x 31.5mm)	Manufacturer	Phihong USA
Package - Series PSM36W Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 89 ~ 270 VAC Voltage - Output 12V Current - Output (Max) 3A Power (Watts) 36W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mm Size / Dimension 4.72" L x 1.98" W x 1.27" H (120.0mm x 50.0mm x 31.5mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSM36WRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input89 ~ 270 VACVoltage - Output12VCurrent - Output (Max)3APower (Watts)36WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 45°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mmSize / Dimension4.72" L x 1.98" W x 1.27" H (120.0mm x 50.0mm x 31.5mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 89 ~ 270 VAC Voltage - Output 12V Current - Output (Max) 3A Power (Watts) 36W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mm Size / Dimension 4.72" L x 1.98" W x 1.27" H (120.0mm x 50.0mm x 31.5mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 89 ~ 270 VAC Voltage - Output 12V Current - Output (Max) 3A Power (Watts) 36W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mm Size / Dimension 4.72" L x 1.98" W x 1.27" H (120.0mm x 50.0mm x 31.5mm)	Series	PSM36W
Input TypeCord (Sold Separately)Voltage - Input $89 \sim 270 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 3A Power (Watts) 36W No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mmSize / Dimension 4.72°L x 1.98" W x 1.27" H (120.0mm x 50.0mm x 31.5mm)	Region Utilized	International
Voltage - Input $89 \sim 270 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 3A Power (Watts) 36W No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mm Size / Dimension 4.72°L x 1.98° W x 1.27° H (120.0mm x 50.0mm x 31.5mm)	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 3A Power (Watts) 36W No Load Power Consumption 300mW (Max) Polarization Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mm Size / Dimension 12V 3A 12V 12V 12V 12V 12V 12V 12V 13A 13A 13A 13B 13C 13C 13C 13C 13C 13C 13C	Input Type	Cord (Sold Separately)
Current - Output (Max) 3A Power (Watts) 36W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mm Size / Dimension 4.72" L x 1.98" W x 1.27" H (120.0mm x 50.0mm x 31.5mm)	Voltage - Input	89 ~ 270 VAC
Power (Watts) $36W$ No Load Power Consumption $300mW$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}C \sim 45^{\circ}C$ Output ConnectorBarrel Plug, $2.1mm$ I.D. x $5.5mm$ O.D. x $11.2mm$ Size / Dimension 4.72 " L x 1.98 " W x 1.27 " H ($120.0mm$ x $50.0mm$ x $31.5mm$)	Voltage - Output	12V
No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mm Size / Dimension 4.72" L x 1.98" W x 1.27" H (120.0mm x 50.0mm x 31.5mm)	Current - Output (Max)	3A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mm Size / Dimension $4.72^{\circ}\text{L} \times 1.98^{\circ}\text{W} \times 1.27^{\circ}\text{H} (120.0\text{mm} \times 50.0\text{mm} \times 31.5\text{mm})$	Power (Watts)	36W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mm Size / Dimension $4.72^{\circ}\text{L} \times 1.98^{\circ}\text{W} \times 1.27^{\circ}\text{H} (120.0\text{mm} \times 50.0\text{mm} \times 31.5\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mm Size / Dimension $4.72^{\circ}\text{L} \times 1.98^{\circ}\text{W} \times 1.27^{\circ}\text{H} (120.0\text{mm} \times 50.0\text{mm} \times 31.5\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mm Size / Dimension $4.72^{\circ}\text{L} \text{ x } 1.98^{\circ}\text{W} \text{ x } 1.27^{\circ}\text{H} (120.0\text{mm x } 50.0\text{mm x } 31.5\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mm Size / Dimension 4.72" L x 1.98" W x 1.27" H (120.0mm x 50.0mm x 31.5mm)	Efficiency	Level V
Size / Dimension 4.72" L x 1.98" W x 1.27" H (120.0mm x 50.0mm x 31.5mm)	Operating Temperature	0°C ~ 45°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.2mm
Report errors?	Size / Dimension	4.72" L x 1.98" W x 1.27" H (120.0mm x 50.0mm x 31.5mm)
		Report errors?

PSM36W-120-TW2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSM36W-120-TW2 Payment Methods





















PSM36W-120-TW2 Shipping Methods













If you have any question about PSM36W-120-TW2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com