

PSU4330 Information



For Reference Only

Part Number PSU4330

Manufacturer Cornell Dubilier Electronics (CDE)

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 43UF 330V QC TERM

Package Radial, Can - QC Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSU4330 Specifications

Manufacturer Part Number PSU4330 Manufacturer Cornell Dubilier Electronics (CDE) Category Capacitors Package Radial, Can - QC Terminals Series PSU Capacitance 43μF Tolerance -0%, +20% Voltage - Rated 330V ESR (Equivalent Series Resistance) - Lifetime @ Temp. -40°C ~ 65°C Polarization Bi-Polar Applications Motor Start Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.438" Dia (36.53mm) Height - Seated (Max) 3.435" (87.25mm)		
CategoryCapacitorsPackageRadial, Can - QC TerminalsSeriesPSUCapacitance43µFTolerance-0%, +20%Voltage - Rated330VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-40°C ~ 65°CPolarizationBi-PolarApplicationsMotor StartRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.438" Dia (36.53mm)	Manufacturer Part Number	PSU4330
PackageRadial, Can - QC TerminalsSeriesPSUCapacitance43μFTolerance-0%, +20%Voltage - Rated330VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-40°C ~ 65°CPolarizationBi-PolarApplicationsMotor StartRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.438" Dia (36.53mm)	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadial, Can - QC TerminalsSeriesPSUCapacitance43μFTolerance-0%, +20%Voltage - Rated330VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-40°C ~ 65°CPolarizationBi-PolarApplicationsMotor StartRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.438" Dia (36.53mm)	Category	Capacitors
SeriesPSUCapacitance $43\mu F$ Tolerance $-0\%, +20\%$ Voltage - Rated $330V$ ESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature $-40^{\circ}C \sim 65^{\circ}C$ PolarizationBi-PolarApplicationsMotor StartRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension 1.438° Dia $(36.53mm)$		Aluminum Electrolytic Capacitors
Capacitance43μFTolerance-0%, +20%Voltage - Rated330VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-40°C ~ 65°CPolarizationBi-PolarApplicationsMotor StartRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.438" Dia (36.53mm)	Package	Radial, Can - QC Terminals
Tolerance -0%, +20% Voltage - Rated 330V ESR (Equivalent Series Resistance) - Lifetime @ Temp Operating Temperature -40°C ~ 65°C Polarization Bi-Polar Applications Motor Start Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.438" Dia (36.53mm)	Series	PSU
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 65°C Polarization Bi-Polar Applications Motor Start Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension 330V -40°C ~ 65°C -40°C ~ 6	Capacitance	43μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 65°C Polarization Bi-Polar Applications Motor Start Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension - 1.438" Dia (36.53mm)	Tolerance	-0%, +20%
Lifetime @ Temp. Operating Temperature -40°C ~ 65°C Polarization Bi-Polar Applications Motor Start Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension - 1.438" Dia (36.53mm)	Voltage - Rated	330V
Operating Temperature -40°C ~ 65°C Polarization Bi-Polar Applications Motor Start Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension -40°C ~ 65°C Bi-Polar -40°C ~ 65°C	ESR (Equivalent Series Resistance)	-
Polarization Bi-Polar Applications Motor Start Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.438" Dia (36.53mm)	Lifetime @ Temp.	-
Applications Motor Start Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.438" Dia (36.53mm)	Operating Temperature	-40°C ~ 65°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.438" Dia (36.53mm)	Polarization	Bi-Polar
Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.438" Dia (36.53mm)	Applications	Motor Start
Impedance-Lead Spacing-Size / Dimension1.438" Dia (36.53mm)	Ripple Current - Low Frequency	-
Lead Spacing-Size / Dimension1.438" Dia (36.53mm)	Ripple Current - High Frequency	-
Size / Dimension 1.438" Dia (36.53mm)	Impedance	-
, ,	Lead Spacing	-
Height - Seated (Max) 3.435" (87.25mm)	Size / Dimension	1.438" Dia (36.53mm)
	Height - Seated (Max)	3.435" (87.25mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Chassis Mount	Mounting Type	Chassis Mount
Package / Case Radial, Can - QC Terminals	Package / Case	Radial, Can - QC Terminals
Report errors?		Report errors?

PSU4330 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSU4330 Payment Methods





















PSU4330 Shipping Methods













If you have any question about PSU4330, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com