

### **PSU6435 Information**



For Reference Only

Part Number PSU6435

Manufacturer Cornell Dubilier Electronics (CDE)

**Category** Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 64UF 250V QC TERM

Package Radial, Can - QC Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **PSU6435 Specifications**

Manufacturer Part Number         PSU6435           Manufacturer         Cornell Dubilier Electronics (CDE)           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - QC Terminals           Series         PSU           Capacitance         64µF           Tolerance         -0%, +20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           ESR (Equivalent Series Resistance)         -           Operating Temperature         -0°C ~ 65°C           Polarization         Bi-Polar           Applications         Motor Start           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         -           Size / Dimension         1.438" Dia (36.53mm)           Height - Seated (Max)         3.435" (87.25mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - QC Terminals		
Category Category Aluminum Electrolytic Capacitors Package Radial, Can - QC Terminals Series PSU Capacitance 64µF Tolerance -0%, +20% Voltage - Rated 250V ESR (Equivalent Series Resistance) -Lifetime @ TempOperating Temperature -40°C ~ 65°C Polarization Bi-Polar Applications Motor Start Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension 1.438" Dia (36.53mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - QC Terminals	Manufacturer Part Number	PSU6435
PackageRadial, Can - QC TerminalsSeriesPSUCapacitance64μFTolerance-0%, +20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-40°C ~ 65°CPolarizationBi-PolarApplicationsMotor StartRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.438" Dia (36.53mm)Height - Seated (Max)3.435" (87.25mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - QC Terminals	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadial, Can - QC TerminalsSeriesPSUCapacitance64μFTolerance-0%, +20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-40°C ~ 65°CPolarizationBi-PolarApplicationsMotor StartRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.438" Dia (36.53mm)Height - Seated (Max)3.435" (87.25mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - QC Terminals	Category	Capacitors
Series         PSU           Capacitance         64µF           Tolerance         -0%, +20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         -           Operating Temperature         -40°C ~ 65°C           Polarization         Bi-Polar           Applications         Motor Start           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         -           Size / Dimension         1.438" Dia (36.53mm)           Height - Seated (Max)         3.435" (87.25mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - QC Terminals		Aluminum Electrolytic Capacitors
Capacitance64μFTolerance-0%, +20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-40°C ~ 65°CPolarizationBi-PolarApplicationsMotor StartRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.438" Dia (36.53mm)Height - Seated (Max)3.435" (87.25mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - QC Terminals	Package	Radial, Can - QC Terminals
Tolerance -0%, +20%  Voltage - Rated 250V  ESR (Equivalent Series Resistance) - Lifetime @ Temp Operating Temperature -40°C ~ 65°C  Polarization Bi-Polar Applications Motor Start  Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.438" Dia (36.53mm)  Height - Seated (Max) 3.435" (87.25mm)  Surface Mount Land Size - Mounting Type Chassis Mount  Package / Case Radial, Can - QC Terminals	Series	PSU
Voltage - Rated 250V  ESR (Equivalent Series Resistance) - Lifetime @ Temp Operating Temperature -40°C ~ 65°C  Polarization Bi-Polar Applications Motor Start Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.438" Dia (36.53mm) Height - Seated (Max) 3.435" (87.25mm)  Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - QC Terminals	Capacitance	64μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  -40°C ~ 65°C  Polarization  Applications  Motor Start  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Pace A0°C ~ 65°C  -40°C ~ 60°C	Tolerance	-0%, +20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 65°C  Polarization  Bi-Polar  Applications  Motor Start  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  -40°C ~ 65°C  -4	Voltage - Rated	250V
Operating Temperature Polarization Bi-Polar Applications Motor Start  Ripple Current - Low Frequency Ripple Current - High Frequency	ESR (Equivalent Series Resistance)	-
Polarization Bi-Polar  Applications Motor Start  Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.438" Dia (36.53mm)  Height - Seated (Max) 3.435" (87.25mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - QC Terminals	Lifetime @ Temp.	-
Applications Motor Start  Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.438" Dia (36.53mm)  Height - Seated (Max) 3.435" (87.25mm)  Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - QC Terminals	Operating Temperature	-40°C ~ 65°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.438" Dia (36.53mm) Height - Seated (Max) 3.435" (87.25mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - QC Terminals	Polarization	Bi-Polar
Ripple Current - High Frequency Impedance	Applications	Motor Start
Impedance - Lead Spacing - Size / Dimension 1.438" Dia (36.53mm) Height - Seated (Max) 3.435" (87.25mm) Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - QC Terminals	Ripple Current - Low Frequency	-
Lead Spacing-Size / Dimension1.438" Dia (36.53mm)Height - Seated (Max)3.435" (87.25mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - QC Terminals	Ripple Current - High Frequency	-
Size / Dimension 1.438" Dia (36.53mm)  Height - Seated (Max) 3.435" (87.25mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - QC Terminals	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - QC Terminals	Lead Spacing	-
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - QC Terminals	Size / Dimension	1.438" Dia (36.53mm)
Mounting Type Chassis Mount Package / Case Radial, Can - QC Terminals	Height - Seated (Max)	3.435" (87.25mm)
Package / Case Radial, Can - QC Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - QC Terminals
		Report errors?

### **PSU6435 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **PSU6435 Payment Methods**





















### **PSU6435 Shipping Methods**













If you have any question about PSU6435, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com