



PT00001R Information

Heisener.com

Part Number PT00001R

ManufacturerRed Lion ControlsCategorySensors, Transducers

Pressure Sensors, Transducers

Description 2 WIRE RELATIVE BAR 0-1 PSI

Package Cylinder

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PT00001R Specifications

Manufacturer Part Number PT00001R Manufacturer Red Lion Controls Category Sensors, Transducers Package Cylinder Series - Pressure Type - Operating Pressure 14.5 PSI (100 kPa) Output Type - Output 4 mA ~ 20 mA Accuracy ±0.3% Voltage - Supply 8 V ~ 33 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features - Termination Style M12 Maximum Pressure - Operating Temperature -40°C ~ 150°C Package / Case Cylinder Supplier Device Package -		
Category Sensors, Transducers Pressure Sensors, Transducers Package Cylinder Series - Pressure Type - Operating Pressure 14.5 PSI (100 kPa) Output Type - Output 4 mA ~ 20 mA Accuracy ±0.3% Voltage - Supply 8 V ~ 33 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features - Termination Style M12 Maximum Pressure - Operating Temperature -40°C ~ 150°C Package / Case Cylinder Supplier Device Package -	Manufacturer Part Number	PT00001R
Package Cylinder Series - Cylonder Pressure Type - Coperating Pressure 14.5 PSI (100 kPa) Output Type - Coutput 4 mA ~ 20 mA Accuracy ±0.3% Voltage - Supply 8 V ~ 33 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features - Termination Style M12 Maximum Pressure - 40°C ~ 150°C Package / Case Cylinder Supplier Device Package - Case	Manufacturer	Red Lion Controls
PackageCylinderSeries-Pressure Type-Operating Pressure14.5 PSI (100 kPa)Output Type-Output4 mA ~ 20 mAAccuracy±0.3%Voltage - Supply8 V ~ 33 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeatures-Termination StyleM12Maximum Pressure-Operating Temperature-40°C ~ 150°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
Series - Pressure Type - Operating Pressure 14.5 PSI (100 kPa) Output Type - Output 4 mA ~ 20 mA Accuracy ±0.3% Voltage - Supply 8 V ~ 33 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features - Termination Style M12 Maximum Pressure - Operating Temperature -40°C ~ 150°C Package / Case Cylinder Supplier Device Package -		Pressure Sensors, Transducers
Pressure Type Operating Pressure 14.5 PSI (100 kPa) Output Type - Output 4 mA ~ 20 mA Accuracy ±0.3% Voltage - Supply 8 V ~ 33 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features - Termination Style M12 Maximum Pressure - Operating Temperature -40°C ~ 150°C Package / Case Supplier Device Package - Supplier Device Package	Package	Cylinder
Operating Pressure Output Type - Output 4 mA ~ 20 mA Accuracy ±0.3% Voltage - Supply 8 V ~ 33 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features - Termination Style M12 Maximum Pressure Operating Temperature Package / Case Supplier Device Package - Cutput 14.5 PSI (100 kPa) 15.8 16.9 16.9 16.9 16.9 16.9 16.9 16.9 16.9	Series	-
Output Type-Output4 mA ~ 20 mAAccuracy±0.3%Voltage - Supply8 V ~ 33 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeatures-Termination StyleM12Maximum Pressure-Operating Temperature-40°C ~ 150°CPackage / CaseCylinderSupplier Device Package-	Pressure Type	-
Output 4 mA ~ 20 mA Accuracy ±0.3% Voltage - Supply 8 V ~ 33 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features - Termination Style M12 Maximum Pressure - Operating Temperature -40°C ~ 150°C Package / Case Cylinder Supplier Device Package -	Operating Pressure	14.5 PSI (100 kPa)
Accuracy ±0.3% Voltage - Supply 8 V ~ 33 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features - Termination Style M12 Maximum Pressure - Operating Temperature -40°C ~ 150°C Package / Case Cylinder Supplier Device Package -	Output Type	-
Voltage - Supply Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features - Termination Style Maximum Pressure Operating Temperature Package / Case Supplier Device Package Supplier Device Package	Output	4 mA ~ 20 mA
Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features - Termination Style M12 Maximum Pressure - Operating Temperature -40°C ~ 150°C Package / Case Cylinder Supplier Device Package -	Accuracy	±0.3%
Port Style Threaded Features - Termination Style M12 Maximum Pressure - Operating Temperature -40°C ~ 150°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	8 V ~ 33 V
Features - Case Cylinder Supplier Device Package - Case -	Port Size	Male - 1/4" (6.35mm) BSP
Termination Style M12 Maximum Pressure - Operating Temperature -40°C ~ 150°C Package / Case Cylinder Supplier Device Package -	Port Style	Threaded
Maximum Pressure-Operating Temperature-40°C ~ 150°CPackage / CaseCylinderSupplier Device Package-	Features	-
Operating Temperature -40°C ~ 150°C Package / Case Cylinder Supplier Device Package -	Termination Style	M12
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 150°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

PT00001R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PT00001R Payment Methods



















PT00001R Shipping Methods













If you have any question about PT00001R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com