

PT00CP-8-2S Information

Heisener.com

Part Number PT00CP-8-2S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 2POS WALL MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PT00CP-8-2S Specifications

Manufacturer Part Number PT00CP-8-2S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 8-2 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert8-2Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Manufacturer Part Number	PT00CP-8-2S
Package-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert8-2Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert8-2Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 8-2 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert8-2Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions2Shell Size - Insert8-2Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert Shell Size, MIL	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Number of Positions	2
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPottedVoltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	8-2
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Termination	Crimp
Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Potted Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold Potted 7.5A	Orientation	N (Normal)
Contact Finish Gold Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	-
Features Potted Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Potted
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

PT00CP-8-2S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PT00CP-8-2S Payment Methods





















PT00CP-8-2S Shipping Methods













If you have any question about PT00CP-8-2S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com