

PT00E-10-5P(SR) Information

Heisener.com

Part Number PT00E-10-5P(SR)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT 5POS WALL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PT00E-10-5P(SR) Specifications

Manufacturer Part NumberPT00E-10-5P(SR)ManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert10-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 10-5 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Voltage - Rated Connectors, Interconnects Circular Connectors MIL-DTL-26482 Series I, PT Receptacles, NeT Receptacle, Male Pins S MIL-DTL-26482 Series I, PT Receptacles, NeT Receptacle, Male Pins S Netherial, Finish Aluminum, Flange Sirain Relief Voltage - Rated Connector Type Aluminum, Olive Drab Cadmium Plated Gold Features Voltage - Rated	Manufacturer Part Number	PT00E-10-5P(SR)
Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 10-5 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Voltage - Rated Convertified Convertif	Manufacturer	Amphenol Industrial Operations
Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 10-5 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 10-5 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated ONLO AMERICAN Series I, PT Receptacle Nall Pins Solder Cup Panel Mount, Flange Solder Cup Bayonet Lock Orientation N (Normal) Gold Contact Finish Gold Strain Relief		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert10-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600 VAC	Package	-
Number of Positions5Shell Size - Insert10-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VAC	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 10-5 Auminum, Flange Fand Sold For a Cup Bayonet Lock N (Normal) Environment Resistant Aluminum, Olive Drab Cadmium Plated Gold Features Strain Relief	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Number of Positions	5
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VAC	Shell Size - Insert	10-5
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Aluminum, Olive Drab Cadmium Plated Gold Strain Relief	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 600VAC	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC	Contact Finish	Gold
	Features	Strain Relief
Current Rating 7.5A	Voltage - Rated	600VAC
	Current Rating	7.5A
Report errors?		Report errors?

PT00E-10-5P(SR) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PT00E-10-5P(SR) Payment Methods



















PT00E-10-5P(SR) Shipping Methods













If you have any question about PT00E-10-5P(SR), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com