

### **PT00E-20-41S(314) Information**

Heisener.com

**Part Number** PT00E-20-41S(314)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 41POS WALL MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

dept@heisener.com

Request a Quote



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## PT00E-20-41S(314) Specifications

| Manufacturer Part NumberPT00E-20-41S(314)ManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A |                          |                                |
|--|--------------------------|--------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A  | Manufacturer Part Number | PT00E-20-41S(314)              |
| Package-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A   | Manufacturer             | Amphenol Industrial Operations |
| Package-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A   | Category                 | Connectors, Interconnects      |
| SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A   |                          | Circular Connectors            |
| Connector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A   | Package                  | -                              |
| Number of Positions41Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A   | Series                   | MIL-DTL-26482 Series I, PT     |
| Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A  | Connector Type           | Receptacle, Female Sockets     |
| Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7   | Number of Positions      | 41                             |
| Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A  | Shell Size - Insert      | 20-41                          |
| Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A   | Shell Size, MIL          | -                              |
| Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Contact Finish  -  Contact Finish  Features  Voltage - Rated  Current Rating  Bayonet Lock  N (Normal)  Environment Resistant  -  600VAC  7.5A   | Mounting Type            | Panel Mount, Flange            |
| Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A  | Termination              | Solder Cup                     |
| Ingress Protection Environment Resistant  Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A  | Fastening Type           | Bayonet Lock                   |
| Shell Material, Finish  Contact Finish  Features  Voltage - Rated  Current Rating  -  Contact Finish  -  -  7  7  7  7  7  7  7  7  7  7  7  | Orientation              | N (Normal)                     |
| Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A   | Ingress Protection       | Environment Resistant          |
| Features - Voltage - Rated 600VAC Current Rating 7.5A  | Shell Material, Finish   | -                              |
| Voltage - Rated 600VAC Current Rating 7.5A   | Contact Finish           | -                              |
| Current Rating 7.5A  | Features                 | -                              |
|  | Voltage - Rated          | 600VAC                         |
| Report errors?   | Current Rating           | 7.5A                           |
|  |                          | Report errors?                 |

### **PT00E-20-41S(314) Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PT00E-20-41S(314) Payment Methods



















## PT00E-20-41S(314) Shipping Methods













If you have any question about PT00E-20-41S(314), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com