

PT00E-24-61S(SR) Information

Heisener.com

Part Number PT00E-24-61S(SR)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

Description CONN RCPT 61POS WALL MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PT00E-24-61S(SR) Specifications

Manufacturer Part Number PT00E-24-61S(SR) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 61 Shell Size - Insert 24-61 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions61Shell Size - Insert24-61Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Manufacturer Part Number	PT00E-24-61S(SR)
Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 61 Shell Size - Insert 24-61 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Voltage - Rated Courrent Rating 7.5A	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 61 Shell Size - Insert 24-61 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7, 5A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 61 Shell Size - Insert 24-61 Shell Size, MIL		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 61 Shell Size - Insert 24-61 Shell Size, MIL	Package	-
Number of Positions61Shell Size - Insert24-61Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Number of Positions	61
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	24-61
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold Contact Finish Gold Strain Relief 7.5A	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Strain Relief
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

PT00E-24-61S(SR) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PT00E-24-61S(SR) Payment Methods





















PT00E-24-61S(SR) Shipping Methods













If you have any question about PT00E-24-61S(SR), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com