



## PT00SE-16-99S(SR) Information

Heisener.com

Part Number PT00SE-16-99S(SR)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 23POS WALL MNT SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PT00SE-16-99S(SR) Specifications

Manufacturer Part Number     PT00SE-16-99S(SR)       Manufacturer     Amphenol Industrial Operations       Category     Connectors, Interconnects       Circular Connectors       Package     -       Series     MIL-DTL-26482 Series I, PT       Connector Type     Receptacle, Female Sockets       Number of Positions     23       Shell Size - Insert     16-99       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Olive Drab Cadmium Plated       Contact Finish     Gold       Features     Strain Relief       Voltage - Rated     600VAC       Current Rating     7.5A, 13A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions23Shell Size - Insert16-99Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Manufacturer Part Number	PT00SE-16-99S(SR)
Package-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions23Shell Size - Insert16-99Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions23Shell Size - Insert16-99Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Category	Connectors, Interconnects
Series  MIL-DTL-26482 Series I, PT  Connector Type Receptacle, Female Sockets  Number of Positions 23  Shell Size - Insert 16-99  Shell Size, MIL		Circular Connectors
Connector Type Receptacle, Female Sockets  Number of Positions 23  Shell Size - Insert 16-99  Shell Size, MIL - Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Gold  Features Strain Relief  Voltage - Rated 600VAC  Current Rating 7.5A, 13A	Package	-
Number of Positions23Shell Size - Insert16-99Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 7.5A, 13A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Features Strain Relief  Voltage - Rated 600VAC Current Rating 7.5A, 13A	Number of Positions	23
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Shell Size - Insert	16-99
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Size, MIL	-
Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  600VAC  Current Rating  7.5A, 13A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Gold  Contact Finish  Gold  Strain Relief  7.5A, 13A	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Ingress Protection	Environment Resistant
Features Strain Relief  Voltage - Rated 600VAC  Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	Strain Relief
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A, 13A
		Report errors?

## PT00SE-16-99S(SR) Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PT00SE-16-99S(SR) Payment Methods



















## PT00SE-16-99S(SR) Shipping Methods













If you have any question about PT00SE-16-99S(SR), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com