

# PT01A-18-30S(SR) Information

Heisener.com

Part Number PT01A-18-30S(SR)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors** 

**Description** CONN RCPT 30POS INLINE SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PT01A-18-30S(SR) Specifications

Manufacturer Part Number     PT01A-18-30S(SR)       Manufacturer     Amphenol Industrial Operations       Category     Connectors, Interconnects       Circular Connectors       Package     -       Series     MIL-DTL-26482 Series I, PT       Connector Type     Receptacle, Female Sockets       Number of Positions     30       Shell Size - Insert     18-30       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Solder Cup       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     -       Shell Material, Finish     Aluminum, Olive Drab Cadmium Plated       Contact Finish     Gold       Features     Strain Relief       Voltage - Rated     600VAC       Current Rating     7.5A, 13A    Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions30Shell Size - Insert18-30Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Manufacturer Part Number	PT01A-18-30S(SR)
Circular Connectors  Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 30 Shell Size - Insert 18-30 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 7.5A, 13A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions30Shell Size - Insert18-30Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 30 Shell Size - Insert 18-30 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions30Shell Size - Insert18-30Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Package	-
Number of Positions30Shell Size - Insert18-30Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating 7.5A, 13A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Bayonet Lock Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Features Strain Relief  Voltage - Rated 600VAC Current Rating 7-Free Hanging (In-Line) Free Hanging (In-Line) Free Hanging (In-Line)  Aluminum, Olive Drab Cadmium Plated  600VAC  7.5A, 13A	Number of Positions	30
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VACCurrent Rating7.5A, 13A	Shell Size - Insert	18-30
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Termination	Solder Cup
Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Gold  Contact Finish  Gold  Strain Relief  7.5A, 13A	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Rating 7.5A, 13A	Ingress Protection	-
Features Strain Relief  Voltage - Rated 600VAC  Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	Strain Relief
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A, 13A
		Report errors?

## PT01A-18-30S(SR) Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PT01A-18-30S(SR) Payment Methods



















# PT01A-18-30S(SR) Shipping Methods













If you have any question about PT01A-18-30S(SR), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com