

## **PT01E-18-32S(302) Information**

Heisener.com

**Part Number** PT01E-18-32S(302)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

**Description** CONN RCPT 32POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## PT01E-18-32S(302) Specifications

Manufacturer Part Number       PT01E-18-32S(302)         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-26482 Series I, PT         Connector Type       Receptacle, Female Sockets         Number of Positions       32         Shell Size - Insert       18-32         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Solder Cup         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       -         Contact Finish       -         Features       -         Voltage - Rated       600VAC         Current Rating       7.5A		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating -  Connectors, Interconnects Circular Connectors  MIL-DTL-26482 Series I, PT Receptacle, Female Sockets  NIV-DTL-26482 Series I, PT Receptacle, PT Receptacle, Female Sockets  - Voltage - Rated 600VAC Current Rating	Manufacturer Part Number	PT01E-18-32S(302)
Circular Connectors  Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Contact Finish Features - Voltage - Rated 600VAC Current Rating 7.5A	Manufacturer	Amphenol Industrial Operations
Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features Voltage - Rated 600VAC Current Rating 7.5A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions32Shell Size - Insert18-32Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions  Shell Size - Insert  18-32  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  -  Contact Finish  -  Features  Voltage - Rated  Current Rating  7.5A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert  Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated Current Rating  18-32  Free Hanging (In-Line) Free Hanging	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features Voltage - Rated 600VAC Current Rating 7.5A	Number of Positions	32
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	18-32
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Contact Finish  Features  Voltage - Rated  Current Rating  Bayonet Lock  N (Normal)  Environment Resistant  -  Convert Rating  Bayonet Lock  N (Normal)  -  Environment Resistant  -  Convert Resistant  -  7.5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A	Termination	Solder Cup
Ingress Protection Environment Resistant  Shell Material, Finish -  Contact Finish -  Features -  Voltage - Rated 600VAC  Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Features  Voltage - Rated  Current Rating  -  Contact Finish  -  -  7  7  7  7  7  7  7  7  7  7  7	Orientation	N (Normal)
Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	-
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	-
Current Rating 7.5A	Features	-
-	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

## **PT01E-18-32S(302) Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PT01E-18-32S(302) Payment Methods



















## PT01E-18-32S(302) Shipping Methods













If you have any question about PT01E-18-32S(302), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com