

PT01W-18-32P Information

Heisener.com

Part Number PT01W-18-32P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

CONTRACTOR CONTRACTOR

Description CONN RCPT 32POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PT01W-18-32P Specifications

Manufacturer Part Number PTOIW-18-32P Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Male Pins Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Male PinsNumber of Positions32Shell Size - Insert18-32Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Manufacturer Part Number	PT01W-18-32P
Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Male Pins Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated Current Rating 7.5A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Male PinsNumber of Positions32Shell Size - Insert18-32Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Male Pins Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions32Shell Size - Insert18-32Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions32Shell Size - Insert18-32Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 600VAC Current Rating 7.5A	Number of Positions	32
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	18-32
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Termination	Solder Cup
Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold 600VAC 7.5A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	-
Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

PT01W-18-32P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PT01W-18-32P Payment Methods





















PT01W-18-32P Shipping Methods













If you have any question about PT01W-18-32P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com