

PT02E-8-4P(009) Information

Heisener.com

Part Number PT02E-8-4P(009)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 4POS BOX MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PT02E-8-4P(009) Specifications

Manufacturer Part NumberPT02E-8-4P(009)ManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Manufacturer Part Number	PT02E-8-4P(009)
Package-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert8-4Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7	Number of Positions	4
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	8-4
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Features Voltage - Rated Current Rating - Contact Finish - - 7.5A	Orientation	N (Normal)
Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	-
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	-
Current Rating 7.5A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

PT02E-8-4P(009) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PT02E-8-4P(009) Payment Methods





















PT02E-8-4P(009) Shipping Methods













If you have any question about PT02E-8-4P(009), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com