

#### PT02SE-22-41S Information

Heisener.com

Part Number PT02SE-22-41S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 41POS BOX MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### PT02SE-22-41S Specifications

| Manufacturer Part Number     PT02SE-22-41S       Manufacturer     Amphenol Industrial Operations       Category     Connectors, Interconnects       Circular Connectors     Circular Connectors       Package     -       Series     MIL-DTL-26482 Series I, PT       Connector Type     Receptacle, Female Sockets       Number of Positions     41       Shell Size - Insert     22-41       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Olive Drab Cadmium Plated       Contact Finish     Gold       Features     -       Voltage - Rated     600VAC       Current Rating     7.5A, 13A       Report errors? |                          |                                     |
|---|--------------------------|-------------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert22-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A  | Manufacturer Part Number | PT02SE-22-41S                       |
| Circular Connectors  Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 41 Shell Size - Insert 22-41 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated Current Rating 7.5A, 13A  | Manufacturer             | Amphenol Industrial Operations      |
| Package-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert22-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A   | Category                 | Connectors, Interconnects           |
| Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 41 Shell Size - Insert 22-41 Shell Size, MIL  |                          | Circular Connectors                 |
| Connector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert22-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A   | Package                  | -                                   |
| Number of Positions41Shell Size - Insert22-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A   | Series                   | MIL-DTL-26482 Series I, PT          |
| Shell Size - Insert Shell Size, MIL   | Connector Type           | Receptacle, Female Sockets          |
| Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A   | Number of Positions      | 41                                  |
| Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A, 13A  | Shell Size - Insert      | 22-41                               |
| Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A   | Shell Size, MIL          | -                                   |
| Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A   | Mounting Type            | Panel Mount, Flange                 |
| Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A   | Termination              | Crimp                               |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A  | Fastening Type           | Bayonet Lock                        |
| Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Gold  | Orientation              | N (Normal)                          |
| Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A  | Ingress Protection       | Environment Resistant               |
| Features - Voltage - Rated 600VAC Current Rating 7.5A, 13A  | Shell Material, Finish   | Aluminum, Olive Drab Cadmium Plated |
| Voltage - Rated 600VAC Current Rating 7.5A, 13A   | Contact Finish           | Gold                                |
| Current Rating 7.5A, 13A  | Features                 | -                                   |
|   | Voltage - Rated          | 600VAC                              |
| Report errors?  | Current Rating           | 7.5A, 13A                           |
|   |                          | Report errors?                      |

#### PT02SE-22-41S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# PT02SE-22-41S Payment Methods



















# **PT02SE-22-41S Shipping Methods**













If you have any question about PT02SE-22-41S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com