

## PT03E-8-3P Information

Heisener.com

Part Number PT03E-8-3P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 3POS WALL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **PT03E-8-3P Specifications**

Manufacturer Part Number       PT03E-8-3P         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-26482 Series I, PT         Connector Type       Receptacle, Male Pins         Number of Positions       3         Shell Size - Insert       8-3         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Solder Cup         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Olive Drab Cadmium Plated         Contact Finish       Gold         Features       -         Voltage - Rated       600VAC         Current Rating       7.5A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Male PinsNumber of Positions3Shell Size - Insert8-3Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Manufacturer Part Number	PT03E-8-3P
Circular Connectors  Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert 8-3 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated Courrent Rating 7.5A	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-26482 Series I, PT Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert 8-3 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert 8-3 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions3Shell Size - Insert8-3Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions  Shell Size - Insert  8-3  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  -  Voltage - Rated  600VAC  Current Rating  7.5A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Voltage - Rated 600VAC Current Rating 7.5A	Number of Positions	3
Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Gold  Features - Voltage - Rated 600VAC  Current Rating 7.5A	Shell Size - Insert	8-3
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  -  Voltage - Rated  600VAC  Current Rating  7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Termination	Solder Cup
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Gold  Features -  Voltage - Rated 600VAC  Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Gold  600VAC  7.5A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

#### PT03E-8-3P Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PT03E-8-3P Payment Methods





















## **PT03E-8-3P Shipping Methods**













If you have any question about PT03E-8-3P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com