

PT05A-14-18S(009)

PT05A-14-18S(009) Information

Heisener.com	PT05A-14-18S(009) Amphenol Industrial Operations Connectors, Interconnects Circular Connectors CONN PLUG 18POS INLINE SKT - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PT05A-14-18S(009) Specifications

Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Category Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 18 Shell Size - Insert 14-18 Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N(Normal) Ingress Protection - Shell Material, Finish - Contact Finish - Yoltage - Rated -		
CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions18Shell Size - Insert14-18Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Manufacturer Part Number	PT05A-14-18S(009)
Circular ConnectorsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions18Shell Size - Insert14-18Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions18Shell Size - Insert14-18Shell Size, MIL-Mouting TypeFree Hanging (In-Line)Mouting TypeSolder CupFastening TypeBayonet LockOrientationN(Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions18Shell Size - Insert14-18Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions18Shell Size - Insert14-18Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Fastening-Yoltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions18Shell Size - Insert14-18Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert14-18Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Connector Type	Plug, Female Sockets
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACKennen Kating-Kennen Kating-	Number of Positions	18
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Orientation-Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	14-18
TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Shell Size, MIL	-
Fastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Mounting Type	Free Hanging (In-Line)
OrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Termination	Solder Cup
Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Orientation	N (Normal)
Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Ingress Protection	-
Features-Voltage - Rated600VACCurrent Rating7.5A	Shell Material, Finish	-
Voltage - Rated600VACCurrent Rating7.5A	Contact Finish	-
Current Rating 7.5A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

PT05A-14-18S(009) Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PT05A-14-18S(009) Payment Methods



PT05A-14-18S(009) Shipping Methods



If you have any question about PT05A-14-18S(009), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com