

PT06E-18-32S(470) Information

Heisener.com

Part Number PT06E-18-32S(470)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 32POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PT06E-18-32S(470) Specifications

Manufacturer Part Number PT06E-18-32S(470) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC Current Pating 7.5A		
Category Circular Connectors Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Voltage - Rated Convertified Connectors, Interconnects Circular Connectors All MIL-DTL-26482 Series I, PT Plug Femical Sockets NIL-DTL-26482 S	Manufacturer Part Number	PT06E-18-32S(470)
Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Voltage - Rated Convertified Conver	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC		Circular Connectors
Connector Type Plug, Female Sockets Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Package	-
Number of Positions Shell Size - Insert 18-32 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 18-32 18-32 Compact Size And Sold Sold Sold Sold Sold Sold Sold Sol	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Number of Positions	32
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated600VAC	Shell Size - Insert	18-32
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Aluminum, Black Zinc Cobalt Plated Gold Strain Relief	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 600VAC	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 600VAC	Shell Material, Finish	Aluminum, Black Zinc Cobalt Plated
Voltage - Rated 600VAC	Contact Finish	Gold
	Features	Strain Relief
Current Rating 7.5A	Voltage - Rated	600VAC
Current Rating 1.5A	Current Rating	7.5A
Report errors?		Report errors?

PT06E-18-32S(470) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PT06E-18-32S(470) Payment Methods





















PT06E-18-32S(470) Shipping Methods













If you have any question about PT06E-18-32S(470), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com