

PT06E-8-4S(362) Information

Heisener.com

Part Number PT06E-8-4S(362)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG 4POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PT06E-8-4S(362) Specifications

Manufacturer Part Number PT06E-8-4S(362) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 8-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Manufacturer Part Number	PT06E-8-4S(362)
Package-SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert8-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating - 7.5A	Number of Positions	4
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	8-4
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish - Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Features Voltage - Rated Current Rating - Contact Finish - - 7 7 7 7 7 7 7 7 7 7 7	Orientation	N (Normal)
Contact Finish - Features - Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	-
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	-
Current Rating 7.5A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

PT06E-8-4S(362) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PT06E-8-4S(362) Payment Methods



















PT06E-8-4S(362) Shipping Methods













If you have any question about PT06E-8-4S(362), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com