

## **PT06J-12-3S(025) Information**

Heisener.com

Part Number PT06J-12-3S(025)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors** 

**Description** CONN PLUG 3POS INLINE SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PT06J-12-3S(025) Specifications

| Manufacturer Part Number     PT06J-12-3S(025)       Manufacturer     Amphenol Industrial Operations       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-26482 Series I, PT       Connector Type     Plug, Female Sockets       Number of Positions     3       Shell Size - Insert     12-3       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Solder Cup       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     -       Shell Material, Finish     Aluminum, Black Zinc Cobalt Plated       Contact Finish     Gold       Features     Strain Relief       Voltage - Rated     1000VAC       Current Rating     13A |                          |                                    |
|---|--------------------------|------------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert12-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A  | Manufacturer Part Number | PT06J-12-3S(025)                   |
| Package-SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert12-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A   | Manufacturer             | Amphenol Industrial Operations     |
| Package - MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 12-3 Shell Size, MIL - Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 11 Plug Plug Plug Plug Plug Plug Plug Plug  | Category                 | Connectors, Interconnects          |
| SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert12-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A   |                          | Circular Connectors                |
| Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert12-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A   | Package                  | -                                  |
| Number of Positions3Shell Size - Insert12-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A   | Series                   | MIL-DTL-26482 Series I, PT         |
| Shell Size - Insert Shell Size, MIL   | Connector Type           | Plug, Female Sockets               |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum, Black Zinc Cobalt Plated  Contact Finish Features Strain Relief  Voltage - Rated 1000VAC  Current Rating 13A   | Number of Positions      | 3                                  |
| Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum, Black Zinc Cobalt Plated  Contact Finish Gold  Features Strain Relief  Voltage - Rated 1000VAC  Current Rating 13A   | Shell Size - Insert      | 12-3                               |
| Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A  | Shell Size, MIL          | -                                  |
| Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A   | Mounting Type            | Free Hanging (In-Line)             |
| Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A   | Termination              | Solder Cup                         |
| Ingress Protection - Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A  | Fastening Type           | Bayonet Lock                       |
| Shell Material, Finish  Contact Finish  Gold  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum, Black Zinc Cobalt Plated  Gold  Strain Relief  1000VAC  | Orientation              | N (Normal)                         |
| Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A   | Ingress Protection       | -                                  |
| Features Strain Relief  Voltage - Rated 1000VAC  Current Rating 13A   | Shell Material, Finish   | Aluminum, Black Zinc Cobalt Plated |
| Voltage - Rated 1000VAC Current Rating 13A  | Contact Finish           | Gold                               |
| Current Rating 13A  | Features                 | Strain Relief                      |
|   | Voltage - Rated          | 1000VAC                            |
| Report errors?  | Current Rating           | 13A                                |
|   |                          | Report errors?                     |

## PT06J-12-3S(025) Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PT06J-12-3S(025) Payment Methods





















## PT06J-12-3S(025) Shipping Methods













If you have any question about PT06J-12-3S(025), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com