

PT06SE-16-8S(424) Information

Heisener.com

Part Number PT06SE-16-8S(424)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 8POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PT06SE-16-8S(424) Specifications

Manufacturer Part Number PT06SE-16-8S(424) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 8 Shell Size - Insert 16-8 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A	Manufacturer Part Number	PT06SE-16-8S(424)
Package-SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A	Manufacturer	Amphenol Industrial Operations
Package - Series MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 8 Shell Size - Insert 16-8 Shell Size, MIL - Characteristic - Crimp Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 15 Aluminum Miles Sockets MIL-DTL-26482 Series I, PT MIL-DTL	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A	Package	-
Number of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert16-8Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesStrain ReliefVoltage - Rated1000VACCurrent Rating13A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Number of Positions	8
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Shell Size - Insert	16-8
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated Current Rating Aluminum, Nickel Plated, Electroless Gold Strain Relief 1000VAC	Orientation	N (Normal)
Contact Finish Gold Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 1000VAC Current Rating 13A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 1000VAC Current Rating 13A	Contact Finish	Gold
Current Rating 13A	Features	Strain Relief
	Voltage - Rated	1000VAC
Report errors?	Current Rating	13A
		Report errors?

PT06SE-16-8S(424) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PT06SE-16-8S(424) Payment Methods



















PT06SE-16-8S(424) Shipping Methods













If you have any question about PT06SE-16-8S(424), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com