

PT07CE-12-8S Information

Heisener.com

Part Number PT07CE-12-8S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

Description CONN RCPT 8POS JAM NUT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PT07CE-12-8S Specifications

Manufacturer Part Number PTOTCE-12-8S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 12-8 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 12-8 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated Current Rating 7,5A	Manufacturer Part Number	PT07CE-12-8S
Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 12-8 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated Current Rating 7,5A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 12-8 Shell Size, MIL		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 12-8 Shell Size, MIL	Package	-
Number of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert Shell Size, MIL	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 600VAC Current Rating 7.5A	Number of Positions	8
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Size - Insert	12-8
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7,5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold 600VAC 7.5A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

PT07CE-12-8S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PT07CE-12-8S Payment Methods



















PT07CE-12-8S Shipping Methods













If you have any question about PT07CE-12-8S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com