

PT08E-22-36P Information

Heisener.com

Part Number PT08E-22-36P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 36POS INLINE PIN RA

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PT08E-22-36P Specifications

| Manufacturer Part Number PT08E-22-36P Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Plug, Male Pins Number of Positions 36 Shell Size - Insert 22-36 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A | | |
|--|--------------------------|-------------------------------------|
| Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Plug, Male Pins Number of Positions 36 Shell Size - Insert 22-36 Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A | Manufacturer Part Number | PT08E-22-36P |
| Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Plug, Male Pins Number of Positions 36 Shell Size - Insert 22-36 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A | Manufacturer | Amphenol Industrial Operations |
| Package - MIL-DTL-26482 Series I, PT Connector Type Plug, Male Pins Number of Positions 36 Shell Size - Insert 22-36 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A | Category | Connectors, Interconnects |
| Series MIL-DTL-26482 Series I, PT Connector Type Plug, Male Pins Number of Positions 36 Shell Size - Insert 22-36 Shell Size, MIL | | Circular Connectors |
| Connector TypePlug, Male PinsNumber of Positions36Shell Size - Insert22-36Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A | Package | - |
| Number of Positions Shell Size - Insert 22-36 Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 600VAC Current Rating 7.5A | Series | MIL-DTL-26482 Series I, PT |
| Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A | Connector Type | Plug, Male Pins |
| Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Voltage - Rated 600VAC Current Rating 7.5A | Number of Positions | 36 |
| Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A | Shell Size - Insert | 22-36 |
| Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A | Shell Size, MIL | - |
| Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A | Mounting Type | Free Hanging (In-Line), Right Angle |
| Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A | Termination | Solder Cup |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A | Fastening Type | Bayonet Lock |
| Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold Contact Finish Gold | Orientation | N (Normal) |
| Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A | Ingress Protection | Environment Resistant |
| Features - Voltage - Rated 600VAC Current Rating 7.5A | Shell Material, Finish | Aluminum, Olive Drab Cadmium Plated |
| Voltage - Rated 600VAC Current Rating 7.5A | Contact Finish | Gold |
| Current Rating 7.5A | Features | - |
| • | Voltage - Rated | 600VAC |
| Report errors? | Current Rating | 7.5A |
| | | Report errors? |

PT08E-22-36P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PT08E-22-36P Payment Methods





















PT08E-22-36P Shipping Methods













If you have any question about PT08E-22-36P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com